

COLOR BOARD CAMERA

HTC-2H6

SPECIFICATIONS

ITEMS	HTC-2H6
PICK UP DEVICE	1/3" CCD IMAGE SENSOR
PICTURE ELEMENTS H * V	NTSC:771 * 492 – PAL:753 * 582
HORIZONTAL RESOLUTION	More than 540 Lines
HORIZ. SYNC.FREQUENCY	NTSC:15.734kHz. - PAL:15.625 kHz
VERTICAL FREQUENCY	NTSC:59.94Hz - PAL:50Hz
SCANNING SYSTEM	2:1 INTERLACE
SENSITIVITY	0.05 Lux F=2.0
SYNCHORIZATION	Internal
S/N RATIO	more than 48 dB
ELECTRONIC SHUTTER	Up TO 1/100,000 sec. (Linear) Auto
WHITE BALANCE	Auto White Balance
MOLUNT LENS	3.6mm F2.0
GAMMA	0.45
VIDEO OUTPUT	1 Vpp,75 Ohms
AUTO GAIN CONTROL	AUTO
POWER SUPPLY	12V DC (+/- 10%)
POWER CONSUMPTION	150 mA
WEIGHT gr	20
STORAGE TEMPERATURE	-30 to + 60 Degree C
OPERATING TEMPERATURE	-10 to + 50 Degree C

Optional lens : 2.9mm, 6.0mm, 8.0mm, and 12mm lens.

*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Dimensions & Connector

