

DIGITAL COLOR BOARD CAMERA

HTC-2N3/ HTC-2N3S

SPECIFICATIONS

ITEMS	HTC-2N3	HTC-2N3S
PICK UP DEVICE	1/4" CCD IMAGE SENSOR	
PICTURE ELEMENTS H * V	NTSC:512 * 492 – PAL:512 * 582	
HORIZONTAL RESOLUTION	More than 400 Lines	
H. SYNC.FREQUENCY	NTSC:15.734kHz. - PAL:15.625 kHz	
V. SYNC. FREQUENCY	NTSC:59.94Hz - PAL:50Hz	
SCANNING SYSTEM	2:1 INTERLACE	
SENSITIVITY	1 Lux F=2.0	
SYNCHORIZATION	Internal	
S/N RATIO	more than 48 dB	
ELECTRONIC SHUTTER	Up TO 1/100,000 sec. (Linear) Auto	
WHITE BALANCE	Auto White Balance	
MOLUNT LENS	3.6mm F2.0	3.7mm corn type pin hole lens
GAMMA	0.45	
VIDEO OUTPUT	1 Vpp,75 Ohms	
AUTO GAIN CONTROL	AUTO	
POWER SUPPLY	12V DC (+/- 10%)	
POWER CONSUMPTION	180 mA	
WEIGHT gr	50	
STORAGE TEMPERATURE	-30 to + 60 Degree C	
OPERATING TEMPERATURE	-10 to + 50 Degree C	

Optional lens : 2.9mm, 6.0mm, 8.0mm, and 12mm lens.

*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Dimensions & Connector

