

HD-CCTV DVR WEBGATE HSC1601F-D Penta-Brid HD Video Recorder Multi Format Supports WEBGATE HSC1601F-D Penta-Brid HD Video Recorder Multi Format Supports

Full HD Digital Video Recorder

HS1600F-D / HSC1601F-D / HSC801F-D

User's Manual (EN Rev 1.0)

HD-CCTV DVR

Install & User Guide

HD-CCTV DVR Manual.

Thank you for purchasing a Webgate Digital Video Recorder.

Before installation or operation please become familiar with the user manual and other referenced manuals mentioned in the booklet.

User manual, software and hardware described here are protected by copyright by law. With the exception of copying for general use within fair use, copying and reprinting of the user manual, either partially or in entirety, or translating it into any another language without the consent of our Corporate office is strictly prohibited.

Product Warranty and Limited Responsibility

The manufacturer does not assume any responsibility concerning the sale of this product and does not delegate any right to any third party to take any responsibility on its behalf. The product warranty does not cover cases of accidents, negligence, alteration, misuse or abuse. No warranty is offered for any attachments or parts not supplied by the manufacturer.

The manufacturer does not assume any responsibility for followings

- ✓ Malfunctions due to negligence by user
- ✓ Deliberate disassembly and replacement by user
- ✓ Connection of power source other than a properly rated power source
- ✓ Malfunctions caused by natural disasters (fire, flood, tidal wave, etc)
- ✓ The warranty period for HDD is one year
- ✓ Any data damage due to HDD damage

The product is not for exclusive use of crime prevention but for assistance in cases as fire or theft. We take no responsibility for damage from any incident.



This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment.

This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause

harmful interference in which case the user will be required to correct the interference at his own expense.



Correct Disposal of This Product (Waste Electrical & Electronic Equipment)

(Applicable in the European Union and other European countries with separate collection systems)

This marking on the product, accessories or literature indicates that the product and its electronic accessories (e.g. charger, headset, USB

cable) should not be disposed of with other household waste at the end of their working life. To prevent possible harm to the environment or human health from uncontrolled waste disposal, please separate these items from other types of waste and recycle them responsibly to promote the sustainable reuse of material resources.

Household users should contact either the retailer where they purchased this product or their local government office, for details of where and how they can take these items for environmentally safe recycling.

where and how they can take these items for environmentally safe recycling.

Business users should contact their supplier and check the terms and conditions of the purchase contract. This product and its electronic accessories should not be mixed with other commercial wastes for disposal.



Correct disposal of batteries in this product

(Applicable in the European Union and other European countries with separate battery return systems.)

This marking on the battery, manual or packaging indicates that the batteries in this product should not be disposed of with other household waste at the end of their working life. Where marked, the chemical symbols Hg, Cd or Pb indicate that the battery contains mercury, cadmium or lead above the reference levels in EC Directive 2006/66. If batteries are not properly disposed of, these substances can cause harm to human health or the environment.

To protect natural resources and to promote material reuse, please separate batteries from other types of waste and recycle them through your local, free battery return system.

Copyright ©2014 WEBGATE. All rights reserved.

Introduction

Warning

Warning

- ✓ Please do not bend or press power cord by force which could lead to fire.
- ✓ Be careful not to pull or plug with wet hands to avoid fire or electric shock.
- ✓ In case of changing built-in lithium battery, it should be replaced with same brand or similar one to prevent a danger of explosion. Since old batteries could be a factor of environment contamination, please disposed of them properly.
- ✓ Do not throw the batteries in fire or heating units. Neither short circuit nor disassembly is prohibited.
- ✓ Do not recharge battery used for remote controller.
- ✓ Do not open the top cover otherwise it could lead to electric shock and product damage.
- ✓ The previous recorded data is deleted if record continues when HDD is full so please check disk setup status.
- ✓ Manufacturer takes no responsibility for any damaged data due to customer's carelessness or negligence.

A-rated device(Broadcasting Communication Equipment for business use only)

Users/Sellers should under this is A-rated device for business use only and it must not be used outside of family.

Caution

- ✓ Do not place heavy objects on top of the product.
- ✓ Product is for indoor use only and it is not water or damp proof. Use product to its environmental specifications (Temperature & Humidity). To clean the product, gently wipe the outside with a clean dry cloth.
- ✓ Product uses AC power of 110V ~ 240V. Be cautious not to cause electric damages to the product.
- ✓ Be careful not to drop the product. Physical shocks may harm the product including internal HDD. In addition, please do not throw or drop it.
- ✓ Product is made of metal you can hurt another human if you throw or used as a weapon. Keep away from the reach of children and install in a safe place.
- ✓ If Product does not operate properly, please contact the closest WEBGATE distributor for service. Tampering or disassembling the product will void the warranty.
- ✓ The product can transmit real time video over network or internet and can be used for monitoring purpose depending on installation sites. So please check and review related regulations before installation.

Experience and technical skills are needed for the installation of this product. Improper installation may cause fire, electric shocks, or defects. Contact the nearest Webgate dealer for installations.

Contents of the manual can differ according to firmware or Software upgrade, and the appearance of products may be changed for the improvement of quality without an advance notice

System power off

In case user turn off device by force while device is working, it could give damage on HDD and device so please turn off device safely using power button located in the front panel. You should install a UPS system for safe operation in order to prevent damage caused by an unexpected power failure.

Working Temperature

The working temperature of the product is 5°C~45°C or 41°F~113°F. DVR may not work properly if left in low temperature for a long period of time. If such is the case, then store at room temperature for some time before using it again.

Contents

Introduction 2

Warning 2

Key Features 5

Specification by Models 6

Components 7

Product Description 8

Installation 13

Connecting other devices 16

Usage 23

Default setting 24

Menu usage 29

Menu structure 29

FUNC menu 29

Monitoring 29

Search and playback 34

Playback 34

Screen composition/names of the functions 35

Copy 36

Configuration 38

System configuration 38

Disk 39

Network 45

Device settings 49

Event Configuration 54

Recording set up 58

Web Viewer 61

System requirement 61

Installation 61

login 61

User set up 61

Monitor 62

Playback 65

JAVA Viewer 68

System requirement 68

Installation 68

Login 68

Monitor 69

Playback 70

Webeye 71 Mobileviewer 71 Appendix 72

Problem solving [FAQ] 72

Compatible HDD 74

Factory default set-up values * 74

Product specification 78

Product Dimension 81

Key Features

Penta-Brid *

Various video format from 1080P, 720P, 960H, NTSC/PAL up to DoubleReachTM can be displayed simultaneously.

It supports real-time live monitoring and record/playback on various format and it records from 5 seconds before event and record up to 30fps per channel.


- ✓ Various video record
 - HD 1080p
 - HD 720P
 - SD 960H
 - SD (NTSC/PAL)
 - DoubleReachTM

Supports manual & schedule recording at all times.

- ✓ Supports archiving event list(sensor, video loss, motion detection, Text)
- ✓ Max 5 seconds pre-alarm recording per each channel

FULL HD

FULL HD high quality video shows far superior resolution than SD video product. Over 1200 TV lines at 1080p resolution can be visible.



DoubleReach™ (Enhances transmission distance by Max. 400m)

It is a technology that increases transmission distance by 400m for HD-SDI cameras.

HD-SDI transmission distance can be reached up to 400m if DR101P-TX, which is DoubleReach transmitter, is connected with HD-SDI camera or if D1080 series camera is connected directly to Penta-Brid DVR.

RAID 1/5/10 Levels *

Supports RAID.


Via RAID MANAGER, various RAID Levels can be configured without additional RAID devices.(RAID 1/5/10)

Surveillance Screens

Every channel will display HD streams without interruptions and will offer many different types of screens.

- ✓ Various Surveillance Screen Mode Single, Multi Screens (1,4,9,10,13,16,CustomA,B,C) *
- ✓ Auto Screen Sequence, Event Pop-up
- ✓ SPOT Single, Multi screen division(1,4,9,16), Auto screen sequence

* Varies between different models



Voice Recording

Supports real time voice input and recording function.

- ✓ Real time 4ch voice input and recording function
- ✓ Input: 4ch RCA, Output: 1ch RCAI(Rear), 1ch HDMI(Rear)
- ✓ Audio recording and playback can be played Simultaneously.

Search and Playback

Various useful functions for search & playback

- ✓ Simultaneous playback for every channel
- ✓ Playback by time, date, channel
- ✓ Time/ Calendar/Event/Thumbnail/Bookmark search
- ✓ Forward/backward search function of a freeze frame

Save and Backup

You can record video data into the internal HDD, and image can be copied to a USB memory.

- ✓ Backup device : USB stick
- ✓ External storage device : e-SATA HDD or NS04R(exclusive storage device) *

Network

Supports LAN, xDSL, and etc., and key functions can easily be controlled by web browser or customized CMS program.

- ✓ HD Live monitoring/playback/backup from the remote site
- ✓ Multi-streaming feature for slow network environment (supports nHD monitoring)
- ✓ Sending event info(image) using E-Mail/ FTP
- ✓ Recorded video playback, save, search function, and DVR control function on PC via CMS
- ✓ Supports 10/100/1000 Mbps Ethernet/xDSL
- ✓ Managing up to 1024 DVRs with CMS

Others

- ✓ User friendly GUI and mouse
- ✓ Easy and simple firmware upgrade, and recorded video back up function using USB stick
- ✓ Using Ac the PC Playback function, replay the DVR's HDD on a PC
- ✓ Supports PTZ control and PRESET function
- ✓ Easy control of up to 255 DVR with a single remote control

Specification by Models

Model	CASE	HDD	DoubleReach	NS04R	RAID
HS1600F-D	Full	SATA*5 + eSATA	Ο	0	0
HSC1601F-D	Middle	SATA*2 + eSATA	Ο	X	X
HSC801F-D	Middle	SATA*2 + eSATA	0	X	X


(O: Supported / X: not-Supported)

^{*} Varies between different models


Components

Please check the below to make sure you have every part.

HS160**0F-D**



HSC1601F-D / HSC801F-D



Product Description


HS160**0F-D**

Front view



	part name	function description	
1	Power	turns ON/OFF the power	
	PWR	It turns on when power is ON	
2	REC	Shows record status while recording	
2	EVENT	Turns on if event is triggered	
	NET	Shows network connection status and it flickers if network is connected	
3	USB port	USB port for flash memory or mouse.	


Rear view



	part name	function description
1	Power Input	AC100V~AC240V power cord socket
2	Ground Connection	Connection terminals that connects DVR to an outside device
3	SPOT	Connection port for SPOT monitor
4	Audio Input/Output	Audio Input : Audio input connection terminal
		Audio Output : Speaker output terminal
5	Sensor, Relay, Com2/3, RS-485 terminating	Sensor: External sensor input terminal
	resisters	Relay: Relay connect terminal.
		Com2/3: For connection with RS-485 device.
		Set terminating resisters when using RS-485 method.
6	COM1	RS-232C D-SUB
7	eSATA port	For connection with external eSATA HDD.
8	Channel Input	Camera input BNC port for 1080P, 720P, 960H, NTSC/PAL, DR cameras
9	HDMI Output	HDMI monitor connection output port
10	Ethernet, Storage	Ethernet : network connecting terminal (RJ-45)
10		Storage: Exclusive network storage device(NS04R) is connected and used.
11	VGA Output	VGA monitor connection output port.

HSC1601F-D / HSC801F-D


Front view



	part name	function description	
1	Power	turns ON/OFF the power	
	PWR	It turns on when power is ON	
2	REC	Shows record status while recording.	
2	EVENT	Turns on if event is triggered	
NET Shows network connection status and it flickers if network is connected		Shows network connection status and it flickers if network is connected	
3	USB port	USB port for flash memory or mouse.	

HSC1601F-D

Rear view




	part name	function description
1	Power Input	Connection socket for DC 12V power code
2	Ground Connection	Connection terminals that connects DVR to an outside device
3	SPOT	Connection port for SPOT monitor
4	Audio Input/Output	Audio Input : Audio input connection terminal
		Audio Output : Speaker output terminal
5	Sensor, Relay, Com2/3, RS-485	Sensor : External sensor input terminal
	terminating resisters	Relay: Relay connect terminal.
		Com2/3: For connection with RS-485 device.
		Set terminating resisters when using RS-485 method.
6	COM1	RS-232C D-SUB
7	eSATA port	For connection with external eSATA HDD.

	part name	function description
8	Channel Input	Camera input BNC port for 1080P, 720P, 960H, NTSC/PAL, DR cameras
9	HDMI Output	HDMI monitor connection output port
10	Ethernet	Ethernet : network connecting terminal (RJ-45)
11	VGA Output	VGA monitor connection output port.

HSC801F-D

Rear view




	part name	function description
1	Power Input	Connection socket for DC 12V power code
2	Ground Connection	Connection terminals that connects DVR to an outside device
3	SPOT	Connection port for SPOT monitor
4	Audio Input/Output	Audio Input : Audio input connection terminal
		Audio Output : Speaker output terminal
5	Sensor, Relay, Com2/3, RS-485	Sensor : External sensor input terminal
	terminating resisters	Relay : Relay connect terminal.
		Com2/3 : For connection with RS-485 device.
		Set terminating resisters when using RS-485 method.
6	COM1	RS-232C D-SUB
7	eSATA port	For connection with external eSATA HDD.
8	Channel Input	Camera input BNC port for 1080P, 720P, 960H, NTSC/PAL, DR cameras
9	HDMI Output	HDMI monitor connection output port
10	Ethernet	Ethernet : network connecting terminal (RJ-45)
11	VGA Output	VGA monitor connection output port.


10

Remote control


Can use every function of the DVR and control several DVRs with only one remote control. To be able to use the remote control, please create a user ID on the remote control ID section of system settings. (See the right picture for working angle of a remote control)



Horizontal Angle: \pm 30° Vertical Angle: \pm 30°



Remote control A



Remote control B

Installation

Check settings

This DVR is high quality security device with a high capacity built-in HDD and important curcuits. Before installation, please read carefully below recommendations as high internal temperature of the product can lead to damages and shorten product life cycle.

Recommendations on installing a DVR in a rack.


- 1. Don't seal the inside of rack where DVR is installed.
- 2. Keep airflow through inlet and outlet.
- 3. If there is another device installed in the rack, secure additional space or install air ventilation.
- 4. Installation of an air circulation fan around each inlet and outlet is strongly recommended. (Install filter around inlet or outlet for harmful substances)
- 5. Keep ambient temperature between 5°C~45°C around DVR.

Warnings if HDD is installed


- 1. Please be extra careful not to damage HDD as it easily breaks.
- 2. During installation, make sure insulated coat doesn't come off or isn't placed in the worng place.
- 3. Don't lose screws and parts.
 - (If screws an parts are not screwed or assembled correctly, product may not operate)
- 4. Check HDD compatibility list HDD
 - (Please check with CS team)
- 5. Partition table must be removed for HDDs used in PC or other DVR models before installation.

HDD installation HS1600F-D


1. Unscrew bracket screws that are fixing it to a DVR..




2. Push HDD bracket to a direction shown in the right picture and separate from fixtures.



1. Lift HDD bracket to a direction shown in the right picture and separate from the bottom.



2.Place HDD in a HDD bracket and fasten 4 screws on each side.




3. Place HDD bracket fastened with screws in DVR and fasten it on the bottom with screws.

<Note>

Below is SATA cable socket sequence of a mainbaord.


Up to 5 HDDs can be installed inside DVR.

Main Board	Disk Manager
INT A	INT A
INT B	INT B
INT C	INT C
INT D	INT D
INT E	INT E
eSATA	eSATA



HSC1601F-D / HSC801F-D

1. Tighten the both side of HDD bracket using screws.




2. Install HDD bracket with HDD into DVR then hold it with screw to fix it to the bottom part of DVR.

<Note>

Socket arrangement of SATA cable in main b'd is as follows.

Two HDDs can be installed in DVR.

Main b'd socket	Disk manager
INT A	INT A
INT B	INT B
eSATA	eSATA



Adding HDD

Remove the power cord before installation to protect DVR against possible damage and an electric shock Please call the store you purchased the product from if it isn't operating correctly due to installation or configuration mistakes.

✓ Warnings regarding Data loss

Please handle with care so HDD data isn't damaged.

Check HDD compatibility before installing additional HDD.

Be careful not to give any shock on HDD during operation which could lead to possible damage or malfunction

✓ Cases when HDD and its data can be damaged.

To minimize the data loss, please copy data as often as you can.


Physical shock during disassembly or installation may lead to Data damage.

Sudden power outage or turn off of DVR can damage HDD.

Please don't try to move or shock DVR while HDD is working.

Connecting other devices

Basic connections



Connecting a monitor

Check monitor resolution and connect to DVR.

✓ HDMI Port : 1920 x 1080p

<Note>

We strongly recommend using HDMI certified cable when connecting to DVR.

Connecting a Camera

Connect 1080P, 720P, 960H, NTSC/PAL camera using recommended cable.

Recommended cable *

Cable Type	HD-SDI transmission	Use
	distance *	
5C2V	about 90M	Analog signal
4C-FB(T), 4C-HFB(T), RG59	about 140M	High-foamed cable, double or triple shielded cables are recommended
5C-FB(T), 5C-HFB, L-6CHD, RG6	about 180M	HD-SDI cable
5C-HFBT	about 200M	HD-SDI cable

^{*} Depends on manufacturer and models.

<warnings>

- ✓ Transmission distance will be affected by cable types and installation site environment
- ✓ Transmission distance of the chosen cable will be various based on reduction rate of 750MHz (reduction rate of dB/100m < 25dB is recommended)
- ✓ Foamed or high-foamed trishield cable is recommended.
- ✓ Impedance 75Ω must be used for coax cable connection and connector work.
- ✓ Beware of deformation of cable due to high pressure over the cable.
- ✓ Don't pull the cable with too much force.
- ✓ For DVR input/output, cables will be tied at the rear of the rack. If tied too tightly, inside/outside insulator can be deformed so tie it loosely within cable's curvature range.

^{*} The transmission distance will be almost doubled in case it is used with WEBGATE's D1080 Series camera or DoubleReach™ Converter

Connecting a power cord

When power cord is connected, DVR starts booting automatically.

How to turn off DVR while it is operating: press power switch for 5 seconds, and a pop-up window will appear, then select "YES" to turn off the power. For turn back on the power again, push the Power button.

Connecting an audio

RCA cable to connect audio input/output devices to DVR

Connecting external device Connecting USB Device

USB port can be used for copy of recorded data and for mouse. See below table for USB Device specifications.

USB specifications	Ver 2.0 or later
Usable device	USB Stick
Voltage specifications	DC 5V / Max. 200mA

<Note>

USB stick needs to be FAT32 formatted.

DVR may not recognize USB Flash memories that require additional program on MS Windows.

Connecting eSATA Device

If external eSATA storage is used, it can be connected to a rear eSATA port. Additional power for eSATA device will be required as DVR doesn't supply power.

<Note> -

- 1. Check compatibility of eSATA with DVR as not all eSATA are compatible with DVR.
- 2. If eSATA is connected to DVR when it is on, it may not be recognized depending on external devices. So we recommend following the below steps.
 - 1) Turn off DVR.
 - 2) Turn off eSATA then connect it to DVR.
 - 3) Turn on eSATA.
 - 4) Turn on DVR.

Connecting NS04R Connecting to DVR

- (1) Connect NS04R to DVR using Gigabit Ethernet cable.
- (2) NS04R's DVR Port and DVR's Storage Port must be connected directly.

<Note> -

- 1) Use Gigabit Ethernet Cable(Category-6) for Network cables to connect to DVR. Other cables are not compatible with Webgate DVR.
- 2) NS04R and DVR must be connected by cables and normal operation isn't guaranteed if Hub is used.

^{*} For more information and setup of NS04R, please refer to "NS04R user manual".


Set ID configuration

Set ID using Rotary switch located at rear panel. Set each different ID in case of over 2 NS04Rs are connected.

Using tool such as Driver to set ID. For Group ID swich, it is set as ID in a unit of 10 when ID switch of NS04R is in a unit of 1.

ID setup value must be within 0~99.

EX) ID will be 23 when switch is set as Group ID=2, NS04R ID=3



<Note> -

1) It approximately takes a minute to turn on the power and to connect NS04R to DVR. While it is connecting, 4 LEDs on the front will be turned on in order and all 4 LEDs may be turned on or off when it is connected to DVR. HDD list can be checked on the disk manager.


Connecting input/out terminalsWire end handling

See below for wire end handling used in terminal block. Please work on single line and multiple line as they have different thicknesses.

- Multiple lines: Peel off the recommended length(8~10mm) and lead-coat it. Use AWG 22 ~ 26.
- Single line : Peel off the recommended length($8\sim10$ mm) and use AWG 20 \sim 26.

Wire insertion/removal

As shown in the picture, push the lever to insert or remove a wire.




Connecting the sensor specification

below requirements need to be met in order to connect the sensor

Specifications	Input Channel #	16EA Transistor input
	Input Type	N.C, N.O support
	Supported sensor	Dry contact sensor
	Connection method	Connect the trimmed wire to terminal block
	Available input	Minimum 500ms
Performance	nce pulse range	
	Output current	Standard DC 12mA

Connecting sensor input terminal

Please see the picture for sensor input. The below picture is an example of connecting Dry Contact sensor type. Please refer to "Wire Handling" for more information.



Connecting relay

specifications


Please see the below table for alarm output requirements.

	Specifications	Output Ch. *	4ch relay output
		Output type Connection	Dry Contact
		Connection method	Connect the trimmed wire to terminal block
	Performance	DC	30V / 1A
		AC	125V / 0.5A

^{*} Varies between different models

Connecting relay


Please refer to the below picture in regards to connecting R1~R4 output. Below picture is an example of connecting a light bar. Please see "wire end handling" in regards to connecting/removing wires.



Connecting COM1 serial port with external devices

Connecting Text input device (ATM / POS / Access Control)

Using COM1/RS232, TEXT DATA can be recorded with synchronizing POS/ATM.




As shown in the picture, for a set up to connect COM1/RS232 (D-Sub 9pin), set up serial & text info under "device" menu.

Connecting COM2/COM3 serial port external device


Connecting serial communication terminal for PTZ device & Keyboard device


Control PTZ devices and Keyboard devices by connecting them to DVR's COM ports. Picture in the right shows how a camera and a keyboard device with PTZ function are connected to RS-232 COM1 & RS-485 COM2 respectively. Other serial communication terminals will be connected to other devices as shown in the below picture.

To connect or remove a wire, please refer to the "wire end handling" and supported models can be checked on "compatible PTZ & Keyboard device" on the supplement booklet.



Connecting Serial Port for Transparent device





Connecting PTZ & Keybaord


up to 255 DVRs can be connected using keyboard and PTZ control is possible for all channels connected to DVR. Also, multiple keyboards extension as Slave can be used limitless with Master Keyboard. In the case, Master Keyboard has priority for all controls. Please refer the instruction manual for PTZ keyboard connection & its way of control which comes with PTZ/ Keyboard.

Configuration using 2 serial ports

PTZ(DOME) and Keyboard can be connected to DVR's 2 serial ports. In such case, keyboard can control DVR and PTZ(DOME) at the same time, and DVR can control PTZ(DOME.

The below diagram represents configuration of multi DVRs with PTZ(DOME). To control PTZ(DOME) using keyboard, please select DVR ID then select camera for control.

control device	connection device
Keyboard (Master/Slave)	All DVRs can be controlled, all PTZ(DOME) can be controlled
DVR	PTZ(DOME) directly connected to DVR can be controlled



Confituration using 1 serial ports


When using 1 serial port, user can connect both of PTZ(DOME) and Keyboard to a port, and user can select a PTZ(DOME) through the keyboard. According to DVR's COM port setting, connected controllable device can be selected, and by choosing a DVR ID, keyboard can control several DVRs.

In case PTZ(DOME) is setup on DVR COM port, user can use it as follows.

Control device	Connection device
Keyboard (Master/Slave)	All DVRs can't be controlled/ All PTZ(DOME) can be controlled
DVR	Only PTZ(DOME) directly connected to DVR can be controlled

In case Keyboard is setup on DVR COM port user can use it as follows

Control device	Connection device
Keyboard (Master/Slave)	All DVRs can be controlled, All PTZ(DOME) can be controlled
DVR	All PTZ(DOME) can't be controlled



Usage

Menu Structure


Press [MENU] key on front panel or click [Main Menu] button under FUNC menu to enter the setup menu. To exit menu, press "X".

Main menu

The selected tab is shown in bright color and the sub-menu box will show the chosen To move to the previous/next tab, use the [◄/▶] arrow buttons. To move to a chosen submenu press the [Enter] key or click on the menu you want to view if you're using a mouse.

Sub-me

Selected sub-menu will disply the chosen item and the related setting will be shown. To move to the previous/next tab, use the $[\blacktriangleleft/\blacktriangleright \triangle/\blacktriangledown]$ arrow buttons. To move to the related setting press [Enter] or click the mouse. To move to the upper main menu, click the [Save Changes] at the bottom of menu, or press [ESC] button.



Set-up dialogue box

The selected tab is shown as orange, and To move to the previous/next tab, use the $[\blacktriangleleft/\blacktriangleright]$ or or click the mouse. To modify the configuration values, click the mouse or use the $[\blacktriangleleft/\blacktriangleright]$

Dialogue box for string input

Dialogue box for string input is shown as follows. User can enter words or numbers using a mouse or direction buttons.

Use $[\blacktriangle/\blacktriangledown]$, $[\blacktriangleleft/\blacktriangleright]$ to move to select a letter and press [Enter] or click a mouse to enter it. To delete the entered letter, press $[\leftarrow]$ button, and to enter a space, press [SPACE] button. To exit the dialogue, press [ENTER] button to save string and exit or press [CANCEL] button to cancel the string.



Default setting

Check video

When turned on, DVR starts booting automatically and shows screen after the booting.

<reference>

Auto login "ON" means login set without any login dialogue box, "OFF" means there will be dialogue box requiring password. (default – auto login ON, admin)





Date & Time settings

Menu \rightarrow system \rightarrow date/time

Standard time zone


Use the left or right arrow key on the front or the mouse wheel to select your time zone. (To go to the previous menu, press the [ESC] button on the front or click "X" with a mouse. This is the same for all OSD menus.)

Daylight Saving Time (DST)

On the "time zone" setting, "on" will be chosen when users click on regions where daylight saving time applies and "off" will be chosen when regions without daylight saving time are chosen.

Users can check "off" if they don't need daylight saving time function for region where daylight saving time applies.

Please select "custom" if users want to set their own daylight saving time preferences. Select "custom" and DST setting will appear. "month/day" will set DST start/end at month/day/hour and "month/week/day" will set DST start/end at month/week/day/hour.



NTP function


Please set NTP 'On' then select 'Public' in Client Mode for DVR to set time automatically via internet connection

Date Notation

Please select "Date Format" and select one of 'YYYY/MM/DD, MM/DD/YYYY or DD/MM/YYYY

Recording configuration

$menu \rightarrow recording \rightarrow recording$



Continuous recording

Continuous recording will automatically begin after the booting is completed and continuous/event recording will begin according to the chosen program values.

Manual recording

Push FUNC [TOOLS – MANUAL RECORDING] on the front to begin/end manual recording and manual/event recording will begin according to the chosen program values.

<reference>

If manual recording is chosen, exit menu and check the manual record indicator on the status bar to confirm recording. If there is no manual recording indicator sign, press FUNC [TOOLS – MANUAL RECORDING] on the front to begin recording.

schedule recording

Schedule recording will begin according to a pre-set day/time schedule.

Set day/time on " schedule setting" under the schedule recording mode.




Program configuration

Menu \rightarrow recording \rightarrow program

Input camera resolution can be checked in "Program" of record setup. User can select program A \sim I to make individual setting on record frame and record quality per program.

<Reference>


How to check if it's recording: If set correctly and is recording, "REC LED" indicator on the front will be flickering. Also, status bar's save indicator will show [SCHEDULE], [MANUAL], or [continuous] indicating that all channels are recording. "REC LED" is turned off when it isn't recording.



Use of Input/Output device Setting sensors

menu \rightarrow event \rightarrow sensor

Please set each and every sensor. Select a sensor, and select a type and click [save] to complete the setting.



Relay setting

$\mathsf{menu} \to \mathsf{event} \to \mathsf{event}$

Select from normal event group, "sensor, motion detect, text, Video Loss" or system event source group, "Disk error, Disk full, Fan error, authentication fail, WRS registration fail, Mirroring fail, abnormal Recording stop" to run relay. Also, user can set working condition by schedule. In case of using control center thru. Network, relay could be run from remotely

Also remote relay control can be made through status&motion relay icon in Control Center.




Copy

сору

In case backup media is well connected, click [Copy] button in FUNC menu and back media is auto detected.

Select copy type \rightarrow Select channel \rightarrow Set copy interval(time) \rightarrow Select drive \rightarrow Start copy.



PTZ

Menu → device → PTZ

At PTZ menu, PTZ's serial port per each channel, Protocol, PTZ address and Baudrate can be configured. Additionally, PTZ home function, Idle time, Parity bit, Stop bit can be configured.




HDD registration and format

menu → system → disk

After mounting HDD and booting, "Disk Manager" will run automatically as shown in the right picture.

If it doesn't run, please check the connectivity of HDD

- (1) Select a HDD among listed HDDs. Activate the HDD and execute format.
- (2) Check "YES" for the fomatted HDD..



<warning>

Please call Webgate or Webgate dealers for HDD compatibility

HDD replacement

- (1) turn off the DVR, take out a HDD and install a new HDD.
- (2) turn on the DVR again, open "Disk Manager". Select the removed HDD, and press [Confirm] to remove the HDD from the list.
- (3) Select the newly installed HDD and format it after completing the activation.
- (4) check the enabled box "YES" for the fomatted HDD.

- <Note>

HDD re-use

You can use HDD that has been used before from DVR, without deleting its data.

Install the previous HDD in the DVR, select from the list and activate it. Enabled box will be checked "yes".

Remote monitoring and control

Via Internet/Intranet, user can use PC to control from the remote site. Enjoy the same control over DVR through PC as you'd have on the spot from the remote site.

Ethernet Connection

Turn off DVR, connect Ethernet cable to DVR and turn it back on.


<reference>

To protect DVR from damage, after connecting Ethernet cable, input Power.

Plug in ethernet cable tightly. Input power on DVR and check its connectivity.

Network configuration

menu → network → network



Ethernet

Click Ethernet for type and enter given IP, Netmask, Gateway, DNS.

xDSL (PPPoE)

Change Network menu type to xDSL then go to xDSL menu. Enter ID and Password assigned from PPPoE registration on xDSL menu. Connection confirmation message will appear when xDSL connection is secured.

DDNS

If DVR is using dynamic IP, use DDNS function to get domain name to access to network regardless of IP change. Enter domain name on DDNS menu. For more information, please go to WNS(www.mycam.to), Webgate's DDNS service website.

WRS

If DVR is using dynamic IP, use WRS service to automatically find the product IP to access. Configure GROUP ID to activate WRS function. Us GROUP ID or SN to Search product in CMS and it is recommended to create an unique GROUP ID configuration to avoid GROUP ID duplication.

Remote control ID configuration


menu → system → tool

When operating more than 1 DVR, it is possible to manage many DVR with one remote control by giving different ID to each and every DVR. A remote control can have maxium of 255 IDs and if users want to use every ID, then select ALL.

Select and control DVRs that have different ID with one remote control.

Selecting remot control ID


- 1) Point a remote control at DVR and press ID on the remote control.
- 2) Press ID on the remote control shown on the screen of DVR.
- 3) Press again ID on the remote control to complete the selection.



Menu usage

Menu structure

Refer to the below picture for The menu structure and read the explanation in each box per item for a set-up guide.



FUNC menu

To run Function menu, please, click the right button of mouse in live monitoring or playback status or push "Func" button on the front panel.

The Function menu enables every function of the product to be controlled by a mouse.

Each function can be executed by clicking left button of mouse.

The Function menu also can be controlled by front part of DVR's buttons.


Please refer to the picture to right for the Function menu structure..



Monitoring

Login screen

DVR will turn on automatically once user connects power to DVR. All LEDs are turn on and off in order when DVR boots up. The basic screen will be black with login window pops up.



Basic screen

The basic screen will be maximum multi screen DVR supports and if rebooted after multi-screen mode has been modified, previous multi-screen mode will be shown.

single screen

click the channel number you want to view or click the left mouse button.

Click [MULTI] button or click the left mouse button again to o return to multi-screen




Multi screen

Click [MULTI] for multi-screen display or press multi under func menu to choose multi-screen mode.



Screen description

The status bar from monitoring screen shows DVR's current status which includes the following: Date/Time, Record status, Motion Detection, sensor input status, text input, Manual Record.



auto switch mode(Sequence)

Auto switch screen mode is a feature in which the selected channel or multi screen division switches in sequence with the time interval of 1-60 seconds.

(Please refer to "Monitor setup" for further configuration method).

Auto Switch mode can be set in every division mode by pressing the [SEQ] button. Press [SEQ] button once more to leave from Auto Switch mode..

event screen

It is available to set the selected screen pop-up automatically when an event is triggered Users can choose events for pop-up from event source. Event source supports 3 types of events: Sensor, Motion Detection & Text.

If multiple events are triggered, the corresponding screens will pop up automatically.

For example, if events are triggered in 3 Channels, they will be displayed in 4 screen division automatically. To return to the original channel, press the button of one of the poped up channels.

Press [ESC] to return to original channel.

<warning>

If Alarm pop-up is "Off", Event pop-up will not be enabled.

If event screen switch is set "Keep", it keeps showing pop-up image until users press a button. To return to the previous screen, please press any button.

Enlarged screen

Using D-Zoom on a single screen, users can enlarge the section they want to view..

Click on [Zoom] button or icon button to activate Zoom mode.


To expand or reduce, please use +, - button or use mouse wheel drag.

The initial location of the enlarged screen is the center. Use the direction keys to move the enlarged image 22 steps to left/right and 14 steps up/down.

Enlarge mode can be used between 1.00X ~ 10.00X range.

"" To return to the previous screen, select a button and press the enter or left click the mouse...

*Zoom function doesn't work in Multi screen mode, please go to single screen mode to use zoom function.



Pausing the live screen

Just like in playback, Live screen can be paused.

Click on [Freeze] button while live monitoring to pause image and to return to live again, please click on any button.

Snapshot picture

Please click on Snapshot while image is Freeze in single live monitoring. Copy them to USB too. Click FUNC menu -> Tool -> Snapshot to copy image to USB memory without stopping or pausing image.

PTZ control

Connect PTZ camera to DVR and set relevant protocol on "PTZ" under MENU, and users can operate PTZ while monitoring live images.

Instant PTZ

If Instant PTZ in Tool menu is set activated, PTZ mode will be on automatically upon single channel, which PTZ function is set. + mark in the center of image will be on while PTZ function is working.



PTZ

When PTZ is on, through PTZ button on front or PTZ buttons under FUNC menu, users can use pan/tilt, zoom, focus, aux and preset functions.

Focus

Click "near", "far" buttons to focus.

zoom

click "In", "Out" buttons to create a preferred focal point.

pan/tilt

pan/tilt function for PTZ configuration channel Use "Up", "Down", "Left", "Right" to control pan/tilt.

Loading preset

Used to move to set preset location.

Select wanted Preset number and press [Load] button.



Saving preset

Use to save new preset location.

Use focus/zoom/pan/tilt to move to a location you want to save it and select a preset number and press [save] button.

Auxiliary On

Use direction keys or mouse wheel to select aux number.(up to 16 Aux functions can be used). Select "on" and press enter or click a mouse)

Auxiliary Off


Use direction keys or mouse wheel to select aux number Aux Select "on" and press enter or click a mouse.

Camera Setup

Use to enter the menu of the connected PTZ device.

Use the front "direction keys" and "enter" button to set up a menu.

Press esc or "o" to exit conso menu.



Bookmark

Add / Edit bookmark No, Time, Channel and Memo in [Tool-Bookmark] of FUNC menu while live or playback.

Run bookmark icon "in Search, Copy, Thumbnail to load saved bookmarks.



Screen Information

Setup or change display information such as channel expression, color, size, status, show/hide/auto hide in [Information-Display] of FUNC menu.



SPOT

Run [Tool-SPOT] in live to select channel to be on SPOT screen or Auto sequence.



Search and playback

Playback

Playback with Basic Screen

- ✓ In monitoring mode, Remote control Press [◄/▶] button to playback the recorded video in full screen
- ✓ If [PLAY] button is pressed, the last playback will run at 1x speed.
- ✓ If [FWD] button is pressed, playback starts from 1min earlier than recent time at 1x speed.
- ✓ If [REW] button is pressed, reverse playback starts from 30 second earlier than recent time at 1x speed.
- ✓ If [PLAY] button is pressed in multi screen mode, playback will start in multi screen mode.

Playback function

button	function	function description
4	playback	Playback 1× speed. When using mouse, click search button under Function menu. If [◀▶]button is pressed in monitor mode, DVR replays from the last replayed position. Pressing [◀▶] button during playback makes reverse replay.
II	pause	Pauses the playback
> >	High-speed forward playback	Different playback speed (in the order of x1, x2, x4, x8, x16, x32, x64, x1, x2, x4)
I	Step forward playback	During playback, Press I ▶ while pressing II to step forward the playback. To return to normal playback mode, press [◀▶]
44	High-speed reverse playback	Different reverse playback speed (in the order of x1, x2, x4, x8, x16, x32, x64, x1, x2, x4)
∢ I	Step reverse playback	During playback, press ◀I while pressing II to step reverse the playback. To return to normal reverse playback mode, press [▶].

Screen composition/names of the functions

Screen composition



name		function description
1	Playback button	Use buttons to control the playback.
2	screen	Displays the playback videos.
2	log viewer	Displays the log seen on timeline
3	Calendar/time search	Select a date on the calendar to view the data of the date.
4	timeline	Displays the info of the unit and search the playback sections.

Icon function description

buttons	description
LIVE	Use to move to live mode.
COPY	Use to COPY
MULTI	Used for multi-screen mode.
THUMBNAIL	Use for Thumbnail search.
	Use for control or manage of playback function.

Time search

Enter the date and time you want to search and press enter to move to the entered date and time.



Calendar search

When calendar search is run, it marks the dates on which there were recordings.

Select a date from calendar you want to search, and it moves to that date.



Event search


Event info(All, Motion, Sensor, Text, None) is shown on timeline. Select a list to move to the selected time.



Thumbnail Search

Thumbnail search will show 35 different thumbnail image on detected images by time interval or motion. Click on selected image for playback or copy.

• Time interval : Select channel to search then set start and end time for search.



Copy

This is for copying recorded videos. There are 2 types of copying, EXE, and AVI.

Only authorized users by security settings can use the Copy function. For more about authority settings, please refer to (user setup) section.

To run copy function, press [COPY] on the product front or Click Copy button under Function menu. If a user runs copy menu during playback, playback time will be set as backup start time.

EXE

Use USB stick to back up and use mini player or control center to playback. It is possible to select a part of channels depending on the choice of the channel list made by a user.



Name	function description		
type	Select EXE using direction keys or mouse wheel.		
channel	Press enter on a channel or right click a mouse to select a channel. (Select All : select all channels / Reset : cancel the selection of all channels)		
format	Format a USB stick before copying. Press Format or right click a mouse to begin. (supports FAT32/NTFS)		

<Warning>

If backup isn't 100% complete, then normal playback on PC isn't possible.

Configuration

System configuration

Please set time/disk/authority.

Date/time

menu → system → date/time

Set the product time in order to set recording settings.

It is very important for DVR to have the right time zone in which it is used for protection of recorded videos.

Default time zone is set at 'UTC 00:00 Dublin".



Time settings

<note>

Under recording, if a user changes time when it is already recording(saved in HDD), it will change the time of the previously recorded videos. Moreover, there will be a history of a time change on the system log.

Standard time zone

Set the timezone to the location a product is used in

daylight saving (DST)

This menu is synchronized with time zone configuration menu. It means only when daylight saving area is on, this function works. Daylight saving applicable area is the same as with Microsoft Windows time zone. Users can select whether to apply daylight savings or not when DVR is installed in Daylight saving applied zone

Date format

Date display settings. Select one of "yy/mm/dd", "mm/dd/yy", "dd/mm/yy.

Save changes

To apply the canges made for date/time, click "date/time apply" button.

<warning>

Other configurations except date/time save automatically, but "date/time" configuration doesn't save automatically since it can critically affect HDD recording file system. To apply the changed value, user must click [date/time apply] button

NTP

menu → system → date/time → Network Time Protocal(NTP)


NTP (Network Time Protocol) synchronizes the time of all connected device. To set DVR time to standard time open server which offers standard time on the network and client which is connected to open server to receive time and synchronize it with standard time. Besides that DVR can be set as server to offer standard time to other devices and can be set as both server and client as well.

NTP server location

Enabled when NTP mode is set as client/server. Select if NTP server is public or local.

NTP local server IP

Enabled when NTP server is set as local and sets server IP address. Enter NTP server IP address located in local network or DVR IP address with NTP mode as a server.



NTP mode

Set DVR NTP mode to client, server or both.

Name	function description	
client	Receives standard time from external or internal server and enable Time synchronization of DVR	
server	Make DVR a NTP server and provide standard time to other DVR or devices.	
both	use both client and server at the same time	

Interval

Configure interval of time sync.

Disk

$\mathsf{menu} \to \mathsf{system} \to \mathsf{disk}$

Sets up a Raid which add/remove/format internal/external hard disk.

Over Write(Auto Deletion)


If there is no space in HDD, old data will be deleted automatically.


Playback block

This function allows only recordings of pre-assigned date to be viewed.

For example, after 10 days of recording(picture 1), if playback block is set at 2 days(picture 2), then as shown

in the picture, only the last 2 days of the recordings can be played back.





Data deletion

This function allows only recordings of preassigned date to be viewed.

For example, if playback block is set at 3 days, then DVR will only save data for 3 days and will delete data more than 3 days old even if auto-deletion isn't on.

Once deleted, it can't be restored so please be extra careful.

Disk manager

$menu \rightarrow system \rightarrow disk \rightarrow disk manager$

This is menu for the management of internal or external HDD. It manages HDD status, bad block, capacity, and whether to use HDD or not.



name	Function description
type	Displays the location and types of a disk.
	Int A (internal A HDD), Int B (internal B HDD), eSATA (external HDD), USB
model	Displays HDD model.
BAD block	Highlights the HDD with BAD block. 0 is shown when there is none. For HDDs not in use, no bad block is displayed.
size	HDD size will be in MB.
S.M.A.R.T	Displays if HDD can be used or not. Good : normal , Bad : abnormal (HDD needs to be replace.)
enable	Displays if HDD is in use or not.
	Yes : can be used / No : can't be used

HDD YES

- select HDD in HDD NO mode and click [enable] button.
- HDD which has previously been used by DVR will be used without formatting and HDD which has never been used will be formatted and then used.

HDD NO

- select HDD in HDD YES mode and click [disable] button.

FORMAT

- can only run when enabled and click [format] after selecting HDD that needs to be formatted.


RAID manager

$menu \rightarrow system \rightarrow disk \rightarrow RAID manager$

This is the menu that manages RAID of internal HDD and HDD installed in NS04R.

Steps to configure RAID

- 1) Select "NO" to all HDD activate in "Disk manager"
- 2) Select device of creating RAID (DVR/NS04R) in RAID MANAGER"
- 3) Select RAID Level(1/5/10) after selecting RAID members.
- 4) Create RAID by clicking "Create RAID" then all selected HDDs will operate in one "DVR RAID Disk"
- 5) If you activate "DVR RAID Disk" in Disk manager" it will be sued as storage of DVR."



name	function description	
Raid Member	Select disks that need to be in Raid.	
Raid Level	Select Raid Level 1, Level 5, Level 10.	
Create Raid	Create Raid with selected Raid Member and Raid Level.	
Raid ID	Displays Raid ID.	
Disk Status	Online : HDD is connected, Offline : HDD is not connected.	

What is RAID?

- ✓ Webgate's DVR models(HD1600F-PDR, HD1600F-R, HD800F-PDR, HD400F-PDR) support RAID function via built-in hard disk.
- ✓ RAID(Redundant Array Independent Disk) can store the data using the pre allocated parity territory if there is an error in hard disk.
- ✓ Supports RAID 1, 5, 10 and auto restore function when replacing a defective hard disk.

Of hard disks and RAID construction methods.

- Depending on the # of hard disks installed in DVR, availability of RAID level will differ.
- ✓ Refer to the below table for supported RAID level.

HDD #	Possible Level	Actual # for recording	Capacity *
2	RAID 1	50%	100% (480fps)
3	RAID 5	66%	66% (320fps)
4	RAID 10	50%	100% (480fps)
5	RAID 5	80%	66% (320fps)

^{*} To use RAID without lowering performance of DVR, configure RAID only with NS04R

How to deal with a problem occurred?

- ✓ If a problem was occurred during RAID operation, RAID manager will appear, and the faulty HDD state will be changed to Offline or Bad from Online.
- ✓ In this case, please turn off DVR and replace the faulty HDD with same capacitor's new HDD. If you turn on the DVR, DVR will start rebuilding automatically. Once rebuilding was started, it will keep rebuilding at background even if you exit the menu. Please note that completion of proper rebuilding can ensure the reliability of RAID system.
- ✓ Please be careful not to replace the normal operation HDD. If you replace the normal operation HDD, you could lost the data. Be sure to replace the faulty HDD only.

User settings

menu \rightarrow system \rightarrow user settings

DVR users will either be manager or user. Managers can use all functions of DVR without limitation and can set up user settings. Up to 10 users can be registered and each user can only use functions for which they've been given access to.



Channel Rights

A manager has an access to every channel.


A manager can give access to channels to each user.



Function access

"Admin" has the rights to all the functions.

The action rights to each function(Playback/Search, Menu, Copy, PTZ, Camera setup, Manual Relay, Power off, Network MIC) can be given by each user.



ID & password change

For User $1\sim10$, max 20 and 8 characters are allowed for ID and Password.

<reference>

Default manager Password is "12345" and for user $1 \sim 10$, password will take a pattern of "11111" for user 1, "22222" for user 2 and so on. So user 10 will have a password of "00000". To enter 0, press "10" on the front panel.

Additional User Setup

- Auto Login On: Select a user that can be automatically logged in when booting.
- Auto Login Off: Login popup will show up when beeting. Video can be monitored after login.
- Auto Logout On: If there is no control of DVR during the selected interval, DVR will be automatically logged out.
- · Auto Logout Off: Auto Logout will not work





Utility

menu → system → utility

Utility sets up DVR name, remote control ID, and language.

DVR alias


Set the DVR alias when connected to network.

language

select a language for a system.

DVR keyboard ID

This menu sets the address of keyboard when using all functions of DVR by keyboard. default value is "1". If user wants to control various DVR by one keyboard, its address should have different value. If designated address is configured the same as keyboard, user can control DVR function.



Remote control ID


Can set up max 255 remote control and all can be managed with a single remote control.

Firmware upgrade

Can update firmware by USB Memory stick

Steps for USB upgrade

- 1) Put firmware file into USB memory and insert it into DVR
- 2) Select "Firmware update" button
- 3) Select "Yes" to the popup "Upgrade firmware from USB disk?"
- 4) DVR will reboot automatically.
- 5) Firmware upgrade completed



System log

System log shows the log list of system booting, user login, setting changes. User can scroll the list using up and down buttons on the front panel.

Factory reset


Change all set up values to default values. Only a manager can use this function.

<warning>

Only a DVR system manager can use this function.


Refer to the (supplement – factor default value) for the factory reset.






Configuration Import/Export

Export – Saves Configuration data in DVR to USB Import – Apply exported Configuration data to relevant DVR or another DVR.



Recording status

Displays DVR recording status.



System info

Displays DVR system info



Network

Configure network info when DVR is connected to a network.

Network settings

menu → network → network → Ethernet

used to configure the relevant network info when DVR is connected to network.

type

Select Network type(Ethernet/xDSL). If DVR is connected to cable modem or lan, select "Ethernet.

If DVR is connected to xDSL, PPPoE type, select xDSL. But if it is not PPPoE type, even if it is xDSL, select 'Ethernet'.

DHCP

If Network to which DVR is connected has a DHCP server, it, assuming it is enabled, will automatically assign IP address to DVR.



IP address

IP Address is for the connection between DVR and Control Center and also for web connection from Webviewer. (But, Net Mask, Gateway should be configured.).

Net Mask

Net Mask makes range of IP address available.

Gateway

Gateway address must be entered for DVR to connect to external network and gateway address is given by network administrator.

DNS server

DNS must be entered in order to use various networks such as, WRS, NTP, e-mail, and twitter. Contact network administrator for DNS address.

UPnP Port Forwarding

When using Internet Sharing device supporting UPnP, this function eable all connected DVR to do Port forwarding and they can be connected to Internet with IP address of Internet Sharing device.

- (1) Configure two DVRs with DHCP On.
- (2) Please, check if DVRs which are connected to Internet Sharing Device are allocated with official IP.
- (3) Configure DVR port of DVR(A) and DVR(B) as 81 and 82 individually.
- (4) Configure UPnP function of Internet Sharing Device as "ON".
- (5) Configure UPnP Port Forwarding function of DVR as "ON".
- (6) Please, check if Port Forwarding Status message is changed from "Not Available" to "Port Mapping is OK".
- (7) Finally, if user accesses DVR(A) with the IP address with port number 81 or DVR(B) with the IP address with port number 82, user can access DVRs.

Port

Register port # in DVR and use it to connect to control center or webviewer.

Default port is 80 and be careful in entering the port # when used with PPPoE modem and router.

Bandwidth limitation.

Bandwidth is to configure the maximum transmission speed. Its default value is unlimited and users don't have to set bandwidth value if there is no need to limit the network data size of DVR.

<warning>

Please consult DVR manager if you want to modify bandwidth value.

RTSP

It is short for Real Time streaming Protocol) and streams real time live image of DVR

Authentification On: Only authorized users can view RTSP video. Authentification Off: Non-authorized users can view RTSP video.

Stream1 : Original resolution Stream2 : Lower resolution

In order to view channel 1 of DVR (Ex: 192.168.1.10) input "rtsp://192.168.1.10/ch1/stream1".

<Notice>

Use VLC player to view RTSP video on PC

IP filtering

Maximum 10 ranges of IP addresses can be set to allow or deny remote network connection

Allow

Allow 192.168.0.0 \sim 192.168.0.255 > another IP addres that does not in the range will not be allowed for remote network connection

Deny


Deny $192.168.0.0 \sim 192.168.0.255 >$ another IP address that does not in the range will be allowed for remote network connection.

<Notice>

IP filtering limits remote connections to DVR Please be aware of what you are doing before you change this page

P2P *

Input UID of P2P connection information in Webeye (Android or iphone) or scan QR code. Remote network connection can be made easily without further configuration.








* P2P function might not be supported depending on the product models

DDNS

$menu \rightarrow network \rightarrow DDNS$

Through Webgate's own DDNS service, WNS server, users can give a domain name to DVR. Using a PC, users can register for a membership and create a domain name even if they don't register at www.mycam.to.

If connected to DDNS correctly, users can connect to status and print connection successful message. If users choose to use Custom instead of WNS, they can register a domain name at www.dyndns.org or www.no-ip.org.



WRS

menu → network → WRS

If DVR is connected to a cable modem or xDSL model, IP address will change every time it tries to connect to ISP and users will not know the changed IP address. However, if DVR with flexible IP address is registered in WRS server, control center can easily access to the registered DVR despite changed IP address

Interval

WRS will renew its IP addresses in WRS server every 5 min if it is activated

group

Group name should closely be related to DVR.


Using a group name, users can find DVR connected to flexible IP on Control Center and connect it

URL

WRS website address is mycam.to.

Status

WRS server registration status of DVR



xDSL

menu → network → network → xDSL

DVR is connected to xDSL line and use PPPoE type, please change type by xDSL and configure user ID and Password. User ID and Password should be same as xDSL.

User ID/Passwor

Configure user ID and Password when DVR is connected to xDSL.

Status

It shows connection status of DVR.



Radius


menu → network → RADIUS

Radius function manages many DVR accounts with one account using Radius server.

Radius menu configures status, IP address, and port. Status should be configured as enable in order to use Radius function. Port by default can use 1812 and if server assigns a port, then it needs to be configured..

'User ID', Password' and 'Radius Shared Key' are needed from administrator of Radius server after forwarding DVR account information to him.

received 'ID/Password/Shared key' are used to register DVR at Control Center.



<warning>

please consult a server manager to use Radius function.

Device settings

In Device setup, user can configure camera, monitor, audio, text, serial which are connected to DVR.

Camera

menu → device → camera

At this menu, user can assign [camera name], and set each camera to use or not to use.

If the operator do not want live monitoring and recording for the video connected channels, the channels must be set as nonuse.



Color Adjustment

AGC, Contrast, Brightness value of connected camera can be adjustable.

<Notice>

AGC function is only for analog(960H, NTSC/PAL) video.



PTZ

Menu → Device → PTZ

Port

Choose one of COM2/COM3/CoC*.

Device

Select a device that is connected to the port.

Address

Select the device's address that is connected to the port.

Baudrate


Select the device's baudrate that is connected to the port.

* Please refer to page 5 for PoC/CoC

PTZ ETC

Preset, Auxiliary and home time can be set up





Preset / Auxiliary

Name and value of preset can be set. Up to 16 presets/auxiliaries can be registered.

Etc

- Home time: In case there is not PTZ control for the selected interval, it moves to PTZ home that was previsouly set in PTZ camera.
- Parity bit/Stop bit/Data bit: Apply the same configuration as configurations of external device

Preset/Auxiliary Setting

- Preset: Load the selected preset, save or delete preset
- · Auxiliary: Turn on or off the selected AUX

<Notice>

COM1 is fixed with RS-232C and COM2/COM3 are fixed with RS-485

Monitor


$menu \rightarrow device \rightarrow monitor$

Configure SEQ, MULTI and event pop up.

alarm pop-up

If specific channel uses MD, Sensor Input, it makes the relevant channel pop-up as single or multi screen. To use this function, event should be set to event schedule in recording set up and MD / Sensor configuration should be done also.

If event popup time is configured "off", event popup will not work. Event pop-up can be configured per second from 1 to 10 seconds. If user set Event pop-up as keep, it will show continuously on the popup screen until the time user push any certain button



Sequence configuration

This menu is to edit function of user sequence configuration. User can configure 16 sequence modes and dwell time is available to set from 5 to 60 seconds.


For sequence mode, users can configure channel or division mode and sequence time from 5 to 60 seconds. If user set it to Off, this function will not work.

The default value of "Restore after Event-Popup" is off. If alarm popup occurs during sequence mode, sequence mode will be stopped under this condition. But, if "Restore after Event-Popup" is on, sequence mode will be activated again after alarm popup time finishes.

Sequence mode starts when user pushes [SEQ] button. To escape from Sequence mode, please, push [SEQ] button one more time.

Multi set-up

Select multi screen order through multi set-up. Maximum of 16 screens can be set-up..





Audio

menu → device → audio

Configure audio channel, audio recording, volume, synchronization, mixing on this menu.

Audio channel

Slelect a channel for audio.

Video channel

Configure if selected audio will be synchronized and heard through the video channel.

For example, if audio channel 1 is synchronized with video channel 4, then audio will be heard through video channel 4.

Save audio

If users want to save the audio in use. If set "off", audio will only be heard with live-video and if set "on", then audio will be heard during the playback

During playback, Audio is output together.



Text

$menu \rightarrow device \rightarrow Text$

Configures text info and click "Text" to configure the text.

Recording

Set On/Off of recording of Text input.

Sync Text with

Select channel to synchronize with text.

device (COM 1)

Choose from Manual, Star Finger 007, VSI Pro for text input device.

Star Finger 007 and VSI Pro can be used with defined protocol, and other devices with Manual mode.

Camera PTZ Monitor Audio Sext Port Device Baudrate Etc. COUIT None 2460 Etc. You can designate a video channel for text device and record the lext data. Sync Video Channel Off On Recording Off On

Manual Text Device Setting

Manual requires header/delimiter/lines/timeouts to be exact. Values for these are different for every device so please call the store you purchased the product from or refer to the manual.

Header check

If Text device is set manually and there is the text pointed out as Header, it is regarded starting of text information from the relevant letter. In case of not using Header, all text after Delimiter is regarded as new text.

Delimiter

It is a constantly inserted info to search for the end of the line. If DVR finds delimiter, it will see the place as the end of the line.

The number of Line

It is to define how many lines single information has. For example, if user sets 30 lines, system recognize single information binding 30 lines.

Time out

If configured line is not full, after the last information, if there is no further information during certain time range, system deal with it as one information.

Event Configuration

Event

menu → event → event

Event set up has 4 set up procedures, event, motion, sensor, and preset.

event

configures time range with event synchronization and can be configured as off, always, and custom

"always" recognizes and reacts to event when it is configured. "custom" can only use event during the time preset based on schedule settings

If custom is configured, event time can be configured per day/time through schedule setting window

If time isn't configured on custom or Off box is checked, DVR won't recognize any event and thus no event motion or event record will run.

User schedule setting

If day/time are set, it will display on the graph right away. Select record begin/end time on the graph and click **them in order**, and the corresponding info will be displayed on day/time.

day : set applicable daytime : set applicable time

register : schedule registration function
delete : schedule unit delete function
Clear : whole schedule delete function

How to delete

Select item and click the Delete button.

If users click the delete button without selecting an item, previously

selected item will be deleted.

How to delete all schedules

Click All Schedule Delete buttion.





Sync event

Configuration for Event synchronization

Relay

When events that have been selected in "Event Sources" occur, event notification by relay goes on for the time period set in "Action time"

Buzzer

Event notification by buzzer goes on for the time period set in "Action time".

E-mail Setup

When events occur, DVR sends text information and image of event to certain email address

FTP

When events occur, DVR sends image of event to deginated FTP server

Video Popup

When events occur, video of event pops up and remain for the time period

Camera preset

When events occur, PTZ preset runs according to previsous settings

Action Time

- Dwelling time of relay or buzzer: Relay or buzzer remain for the selected time preriod
- E-mail : Sends email according to the interval
- FTP, System alarm, camera preset: Always operate on event

<Notice> If Action time is off, action for events will not work.


EVENT SOURCES

Check Sensor, Motion detection, Text or systems for activating event

System event sources of HDD Fail, RAID fail, fan fail, password fail, WRS registration fail and power on can be checked (some or all)



×



E-Mail Configuration

Recipient Address


Input E-mail address with receiver's E-mail info.

Sender's E-mail address

Sender's E-mail address is set when user use E-mail for output selection and user setup E-mail address as xxxx@xxxxxx.xxx.

Picture attachment

When sensor, motion detector and video loss occur, relevant event info with channel video will be sent to an e-mail. Only system event info will be sent for system event.



Authentification

There are a few ways to send email (No authentification, SMTP server authentification and TLS authentification.)

- No authentification: sends email to the recipient address without server authentification
- SMTP authentification: sends email to the recipient after SMTP server authentification. The recipient address must support SMTP authentification
- TLS authentification : sends email to the recipient after TLS server authentification.

FTP Configuration

The DVR sends 1 video image per event to a FTP server when an event occurs.

<warning>

Since FTP just transmits an image, if there is no image system event, it is not supported.

Sever IP/URL FTP_SERVER FTP Directory / User Account ID ftp_user Password •••••••

Server URL

Enter the FTP server address to send image

user ID

Enter the relevant ID when asked for FTP server authentication.

password

enter FTP server password.

FTP Directory

Select Folder to save image

If folder is not indicated, the image is sent to the folder which server selects

Motion detection

$menu \rightarrow event \rightarrow motion$

The Motion detection can be used to notify user of detected motion on each channel or all channel.

Channel

Configure All or each channel.

Sensitivity

Sensitivity can be configured from min.1 to max 10.


Area

Area configure detection when a motion is triggered. User can select all or clear all. In case of configuring each channel, it is available to set all, clear all or define user area.

User area

When selecting a channel, user area can be configured. 1 grid size is **15x10** and factory default value is "All grid selected". Press "change area" button to open motion detector enabled area set up window.

Users can set motion detection area in screen. The motion detection zone by setting is indicated in translucent green.





If an area is set up when motion detector set up start point is enabled, all values will be applied as disabled and if set up when motion detector set up start point is disabled, then all values will be applied as enabled. In other words, opposite set up to the value of the initially selected area will be applied.

Sensor

menu → event → sensor

This menu is to setup the existing sensor input and the type of sensors. If sensor is selected as N.O, or N.C. it is applied to all channels. Users can set different options like N.O, N.C, or Off after selecting each channel.

Name	description		
Normal Open	If sensor's electric contacts become connected,		
	DVR recognizes it as an alarm.		
Normal Close	If sensor's electric contacts become		
	disconnected, DVR recognizes it as an alarm.		



Recording set up

There are 4 modes for recording – schedule recording, manual recording, Continuous Recording, and Event Recording. Schedule Recording records automatically in accordance with the configured schedule and Manual Recording records via pushing FUNC [TOOLS – MANUAL RECORDING] button.

Continuous Recording records continuously upon initial system boot up. Event Recording records when an event occurs

Recording

$menu \rightarrow record \rightarrow record$

Users can select the recording mode from manual, continuous, or schedule recording.

And their resolution, frame rate, quality will be in accordance with the program Before recording set up, check the frame rate, video quality of a program per channel.

Manual recording


Manual record can be made only when record mode is set as manual record.

Manual record start when user click on [TOOLS – MANUAL RECORDING] ini FUNC menu after record mode is set as manual record and to end record, please click on MANUAL RECORDING button again.



Continuous recording


Recording mode must be set at continuous recording and preset program will begin recording once booting is complete.



Schedule recoding

It records according to the programmed schedule automatically. select "Schedule record" and configure day and time

. Check and select each program default value and select one of 9 programs from A to I. User can not set two different program to one schedule.



Configuration

Configure a program, time on a date and the info will automatically be displayed on the graph.

If select recording start/end time the table and click them in order and the corresponding info will be displayed

• Program : Set recording program(A~I)

• Time : Set time to apply

• Registration : Schedule registration

• Delete : Delete a schedule

• All Delete : Deletes the all schedules



deletion

Select items and click Delete button

If clicking delete button without item, previously selected item will be deleted from the latest time order. Clicking All Delete makes all schedule deleted.

<warning>

When configuring time sector, previously configured time can not be included.

Event recording

Event recording is a recording via "sensor", "motion detection", and "text" input.

To perform event recording, frame rate and video quality per program need to be set at program settings. By default, event recording synchronizes with 3 recording modes, continuous recording, manual recording and schedule recording.

<reference>

If user wants to use Event recording only, please, set frame rate as 0fps and enter frame rate for Event recording.

Event applied time

To make event record user needs to setup record time for pre and post event. Event record range will be set based on time set by user.

Record time before event

User can select between 1~5sec and time ahead of event will be recorded as much as time set by user.

Record time after event


User can select between 1~30mins and time after event will be recorded as much as time set by user

Program

menu \rightarrow recording \rightarrow program

Using [Program], adjust frame rate and quality configure recording program for Continuous, Manual, and Schedule recording.

Select Program to configure frame rate & resolution. For maximum performance, user can freely allocate the recording resource per channel. This feature enables the user to lower the recording performance of each channels and allocate the remaining resources to raise the recording performance of a specific channel or channels.



Program

There are 9 programs from A to I composing recording quality and resolution per channel.

Channels

Display the channel No.

video

displays entered video resolution and FRP.

Normal Record

Select frame rate per second and quality that are applied for normal video without events.

Event Record

Select frame rate per second and quality that are applied when event occurs. When event occurs DVR starts to record by the frame rate per second and quality of Event Record.

FPS

FPS (frames per second) users can select 1 to 30fps per second. Max. Frame can be changed according to the configuration.

Quality

This configures the recording quality. Value of Q can be configured between 1-10. The higher the number, the better recording quality is.

Record Capacity Usage

Displays the DVR recording quality.

Quick Setting

Apply the same setting for all channels at once.

<Notice>

Frame rate per second and quality cannot be set exceeding the specification of DVR. Please check the specification of DVR first before setting record.

Web Viewer

WebViewer is Web application program loaded to monitor real-time image or to monitor the images recorded through Web browser to PC located remotely.

System requirement

Items	Recommendation		
CPU	Core i5 3.0GHz		
Main Memory	4GB		
Video Memory	512MB or higher		
Display	1024MB PCI-E Graphic Card Support AGP Accelerate		
BUS	Support PCI-E 16X or highter		
Network	100/1000 Ethernet NIC		
OS	Windows XP Professional(SP3 or higher) / Windows 7		
Browser	Internet Explorer 8 or higher		
Others	DirectX 9.0 or higher		

Installation

Webviewer Installer

Auto installation program is provided from login page to use Webviewer function. ActiveX installation is required to a PC which has first connection.

<caution>

Please close all programs related to Control Center while Webviewer Installer is being installed. Otherwise, it may affect the installation.

login

After inputting an IP address that is set to the system, the WebViewer Login page will be connected. Examples of input method in address box are http://192.168.1.100 as IP address type or www.addresstest.com as domain address. In case of changing the port value besides default value 80, just input the changed port value.

Input the set of User ID & Password, click 'LOGIN' to access. If password didn't change tin Control Center, ID and Password will be admin/12345.




User set up

To access WebViewer, user authority and password can be changed in DVR or the account menu of Control Center configuration.


Monitor

When it is authorized with User ID & Password input at Login page, it moves to monitor page. At Monitor page, monitor real time image of cameras connected to DVR, or it can control PTZ camera, Relay, and use Microphone function according to user's authorization.




screen division and changing video position

The first monitor page will display the maximum screens of the connected model.



It can to change to 1, 4, 9, 13, 16, 25, 36 divisions by clicking the number on top of page.

Also, it can change to 1 channel mode by click any one of channel image.



Double click on one of the playback screen to convert in 1 channel mode

1 After conversion to 1channel mode, double click on screen to return to previous division channels.



At division screen, it can change screen location using mouse drag

If Ch3 image moves to Ch1, drag Ch3 image and drop on Ch1 location so as to exchange between 3ch and

1ch image.

Press the very front icon on the upper screen on multi screen mode to switch to a full screen mode. To go back to normal screen mode from full screen mode, press ESC key

Move to Playback

Click the on the upper right to move to playback page.

channel On/Off

It is On/Off button for the Channel located to left in page. Click the channel wanted to On or Off.

And Default is "On".



Sensor indication

The icon indicates when sensor occurs in system

When it sensors, relevant sensor icon comes to Red, and indicates sensor number of video. When sensor is not triggered, icon keep as blue.



Relay operation

It can On or Off Relay of the unit. Click the number button to activate Relay On, then the icon Changes from Blue to orange color.



Not activated Relay button means, the product is no supported. Relay is need user's authority. Refer to user manual in the unit for the setup of User's authority of Relay.

Using microphone

Microphone can be set On or Off. Default is Off and it is changed from the projected type button to orange when click the button for the use Mic.



Event information

Time		Event	Message	_
2011.03.29 11:27:18	桑	1 On	CH1 - Motion Detected	
2011.03.29 11:27:18	桑	3 On	CH3 - Motion Detected	
2011.03.29 11:27:18	桑	2 On	CH2 - Motion Detected	
2011.03.29 11:27:16	桑	4 On	CH4 - Motion Detected	
2011.03.29 11:27:16	A	3 On	CH3 - Motion Detected	•

It shows real time event data occurred at the bottom of monitoring page. Indicated Event data list are as follow

button	description
#	Motion Detect On
펠, 펠	Sensor Input
5 , 5	Relay Output On
* , *	No Video, Video Detected

video recording & save video recording

Select by clicking "Rec Start" in right button of Mouse after selecting channel user wants to record during monitoring. It can record max. 10 minutes of video During Quick Recording, recording time is indicated on video.

If "Rec Stop" is pressed by clicking right mouse button, recroding stopped. Then, open the dialogue box to store recorded files. At this time, user can save it to the directory with any file name by user.

Saved recording file is saved into "*.re4" file format. re4 file can playback through Control Center Playback program or Mini Player program.



saving video

There are 3 types for saving Video - jpg, bmp, eye, saving means the function to record 1 frame of current monitoring channel.

To save video, select the channel and click right button of mouse. and select "Save As" and point out the location and press Save button.

Using PTZ

During monitoring, select a channel with PTZ configuration and right-click to select "PTZ" to use PTZ. PTZ control lets users use Pan/Tilt, Zoom/Focu functions.

Pan, Tilt control

There is a cross line in the middle and click image to operate Pan, Tilt. In the middle click Left/Right direction to control Pan, and Click Up/Down direction to control Tilt. The further it is clicked from the middle, the faster Pan/Tilt will operate.



Zoom, Focus control

Move mouse to the edge of left & right to see slide bar for Zoom, Focus.

The unit Area Zoom In available has Zoom Zero operating button. It can zoom in/out using slide bar at left of image, left slide bar can control Focus.

Move to Preset

In case of Preset set, Mouse on image press right button for pop-up menu and "Goto Preset" is indicated additionally. When select Preset list, it moves to Preset position selected. Preset should be set up by user in advance.

Activating Auxiliary

In case of Preset set, "Auxiliary" is indicated additionally, and it operates action when select registered menu.

<Reference>

Supported PTZ camera list can be refereed to (PTZ manipulation).

Using Audio

In case of Channel setup sync with Audio, press right mouse button on the image to activate pop-up menu to "Listen" and uncheck Mute. Audio Volue adjustment is available using slide bar.




Playback

This page is to playback recorded images, and user who has authority of 'HDD' among user ID or administrator can use this function.

Playback that is made up 16 divisions can play the images by searching through colander by recording period and moving the period. It can backup recorded image and also print Pause image or save to Bmp file.

Below are each title and function of Playback.



Video Division & Changing Channel



Playback supports 1, 4, 9,16 divisional screens. select division using menu on top of page as shown in the above picture.



Press the very front icon on the upper screen in multi-screen mode to switch to a full screen mode. To back normal screen mode from full screen mode, press ESC key.

Save image



It can save playback image to BMP file.

Click mouse to channel to save. Dotted line will be surrounding to the selected channel, and click 'Save' button

Save imamge dialog box appears, then it can input message or select channel name, date, event and data.

Press 'OK' to open dialog box for the saving location, then save




bmp file.

Print

Select image with mouse for the channel to print image saved, and then click 'Print' button.


Window comes to input Memo, and click 'OK' button to print the image through the printer connected.

Print material includes 'Printing Date', 'Channel name', 'Recording Date' 'Event', 'Memo'.



Back up

There are re4 (Multi channel) and avi(single channel) Set From, To time and select the channel for backup Point out the location for backup. Input in Password/Verify. In case of playback backed up file, correct password should be input.



Move to Web Monitor

Click 'Go' button at top of page, and it can move Web monitor page.

channel On/Off


same function as the Channel On/Off function at Web Monitor. Located on the right, and click the wanted channel to "On" or "Off". All channels are On by Default.

Disabled Channel button means the product doesn't support it.



Saving time & Checking Record Capacity


Displays the used and remaining space of HDD and the dates on which the first recording and last recording were done. It also shows in % how much space a user is using.



Calendar search

Recorded date is enabled in black color, and others unrecorded date disabled in grey. Click [Go to] button after select date & time so as to playback images on the date & time selected.

'When clicking the 'Go To' button, it indicates for 24hours from the time selected at left bottom. As above picture, it is possible to change the time zone with '24h' button.



Function buttons on the bottom of an image



- ① Indicates playback range of recorded image.
- ② Press ←,→ button as the time set at (5) so as to change the time zone to playback in forwarding and reversing.
- ③ From left button, it can 'Move a frame back', 'Play backward', 'Stop', 'Play', 'Move a frame forward'.
- 4 It is the function to set play speed. After click the button, it can set the play speed '0.5x, 1x, 2x, 4x, 16x, 32x, 64x, and All'.
- ⑤ It is the function to set play area. After click the button, it can select play area '10min, 30min, 1hour, 3hour, 6hour, 12hour, 24hour'.
- 6 It can select DirectX use or not. If check DirectX mode, it can play image into Direct Draw based on graphic card and performance of PC.
- 7) It is the function to set audio play or not, and volume

JAVA Viewer

Jave Viewer supports DVR monitoring function regardless of operating system.

System requirement

Items	Recommendation		
CPU	Core i5 3.0GHz		
Main Memory	4GB		
Video Memory	512MB or higher		
Display	1024MB PCI-E Graphic Card Support AGP Accelerate		
BUS	Support PCI-E 16X or highter		
Network	100/1000 Ethernet NIC		
OS	Windows 7 / Windows 8 / OS X Mavericks (version 10.9)		

Installation

Javaviewer Installer

To use features of JavaViewer, please download JViewer.zip file then unzip and run "jviewer_start.jar" file.

<Notice>


Please install Java from www.java.com to use Java Viewer



Login


After inputting an IP address that is set to the system, the WebViewer Login page will be connected. Examples of input method in address box are http://192.168.1.100 as IP address type or www.addresstest.com as domain address. In case of changing the port value besides default value 80, just input the changed port value.

Input the set of User ID & Password, click 'LOGIN' to access. If password didn't change tin Control Center, ID and Password will be admin/12345.



Monitor

When it is authorized with User ID & Password input at Login page, it moves to monitor page. At Monitor page, monitor real time image of cameras connected to DVR, or it can control PTZ camera, Relay, and use Microphone function according to user's authorization.



Screen division and changing video position

The first monitor page will display the maximum screens of the connected model.



It can to change to 1, 4, 9, 16 divisions by clicking the number on top of page.



Single screen

Double click mouse on the channel wish to make single channel

To back to multi screen, please double click again.



Click [] to swith screen into full screen mode. Click on [F11] key to back to normal screen mode.

Playback

Click [Playback] to run playback.

Playback is page, where only Authorized or user account assigned with right for [playback/search] can use.

Playback can be controlled by search, time shift button or click on time line.




Calendar search

Recorded date is enabled in black color, and others unrecorded date disabled in grey. Click $[\rightarrow]$ button after select date & time so as to playback images on the date & time selected.




Record duration and record capacity check

It indicates total recorded capacity and remaining capacity in Hard disk. And it marks record start date till last recorded date. Also it shows amount of Hard diskHDD.



Time line and function button



- (1) is range of time line.
- (2) From left button, it is backward step playback, backward playback, Pause, forward playback, forward step playback button.
- (3) is setup on playback speed. Playback speed set as following "1/2x, 1x, 2x, 4x, 8x, 16x, 32x, 64x, ALL".
- (4) shows recorded information on the timeline and select preferable time to move to search time.

Webeye

Mobile viewer is an Application for Smart Phone. It is available to serach and install as free of charge with "WebEye" keyword in **Apple App store** & **Google Android Store**.

- ✓ Available to register up to 16 units
- ✓ Supports multi-stream function
- ✓ Able to search system and event logs.
- ✓ Supports Digital Zoom, PTZ Control, Image saving, Image e-mail sending, etc. in Single Monitoring Mode.



Mobileviewer

This service allows users to view video by accessing to DVR from mobile device's web browser without certain applications. The device must support either wifi, 3G or Lte.

Input the form of http://IP/svc/mviewer.html to access to DVR from the web browser



Appendix

Problem solving [FAQ]

problem & symptom	solution	
If system power isn't on, LED on the	✓ Check the power of system	
system front won't operate	✓ Check power voltage in out	
	✓ Check or replace power supply if power doesn't turn on after	
	above procedure	
No video on some channels with black	✓ Check the camera connected with relevant channel.	
screen	Occasionally, the symptom may occur if camera video doesn't	
	input correctly.	
	✓ Check if power is supplied to camera correctly.	
	✓ Occasionally, the symptom may occur with weak video signal from	
	video distributor when the video is connected with variable	
	systems. In this case, the symptom can be figured out/ solved	
	connecting the camera directly to DVR.	
No Video on Screen	✓ Check cable between DVR and camera	
	✓ When camera is connected to HD-SDI BNC input:	
	Check if camera support HD-SDI output	
	✓ When HD-SDI BNC output is connected to Monitor BNC directly :	
	Check if monitor support HD-SDI input	
	✓ When HD-SDI video is changed through DVI, VGA, etc. thru video	
	converter : Check if video format of converter's HD-SDI input	
	support s video format of this product.	
REC LED doesn't turn on despite	✓ Check if HDD space is secured to record	
pressing [REC] button in front panel	✓ Check if recording mode is set in menu	
and No recording.		
Only logo screen shows repeatedly	✓ Main board has a problem or SW is damaged. Please contact CS	
	team for a further check.	
Channel button doesn't work in live	✓ If current screen is for event use, channel doesn't work. In this	
screen.	case, please terminate event screen pressing [ESC] and select	
	channel.	
Cursor doesn't move in Calendar	✓ Check if marked at channel and date you want playback	
Search.	✓ Both channel and date should be checked to start playback.	
Alarm doesn't stop in spite of pressing	✓ Please delete alarm pressing Remote Control [MENU] in front	
Remote Control [ESC] button to delete	panel as follows.	
after an alarm is triggered.	1) Withdrawing event monitoring screen : Monitoring mode – It	
	turns off event monitoring time duration.	

2) For alarm sound cancel : Event record mode - Alarm (Motion detection/Video loss) – It erases alarm output. 3) For event cancel : Event record mode - Alarm (Motion detection/Video loss) – It turn off mode. No response in Live screen even FUNC (TOOLS - PTZ) button is pressed. External HDDs are not recognized as quantity installed physically after connecting multiple external HDDs to DVR. **HDD FAIL** icon and error message pops up. **Please check HDD connection status. **Please check HDD connection status. **Please check HDD connection status. **Please check HDD connection. **Please check if additional HDD is compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. **Please check if additional storages are compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. **Please check if additional storages are compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. **Please check if additional storages are compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. **Please check if additional storages are compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. **Please check if additional storages are compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. **Please check if additional storages are compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. **Please check if DVR. To Please contact CS team of manufacturer. **Please install multi codec for playback data copied in avi format. **Please install multi codec for playback data copied in avi format. **Please check if current time		
3) For event cancel : Event record mode - Alarm (Motion detection/Video loss) — It turn off mode. No. response in Live screen even FUNC (TOOLS - PTZ) button is pressed. External HDDs are not recognized as quantity installed physically after connecting multiple external HDDs to DVR. "HDD FAIL" icon and error message pops up. "HDD FAIL" icon and error message rither is no added information of HDD after installing additional HDD. There is no added information of HDD after is no added information of external storage devices (USB memory, eSATA HDD). Network setup using router is difficult. Lost password. Copied data is not played in the PC. Copied data is not played in the PC. Can't return to live mode during playback. Recording is not working. For event cancel : Event record mode - Alarm (Motion detection)—It turns off DVR. Check if connected protocol and other configuration is set correctly for PTZ camera in Menu -> Device -> PTZ. Check if connected protocol and other configuration is set correctly for PTZ camera in Menu -> Device -> PTZ. Check if connected protocol and other configuration is set correctly for PTZ camera in Menu -> Device -> PTZ. Check if connected protocol and other configuration is set correctly for PTZ camera in Menu -> Device -> PTZ. Check if connected protocol and other configuration is set correctly for PTZ camera in Menu -> Device -> PTZ. Check HDD is ready in the DD. There is no added information of HDD problem. Please contact CS team of manufacturer. Please check if additional HDD is compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. Please check to UPnP section under "Network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup. Please contact CS team of manufacturer. Copied data is not played in the PC. Please contact CS team of manufacturer. Please install multi codec for playback data copied in avi format. Please check if camera i		2) For alarm sound cancel: Event record mode - Alarm (Motion
detection/Video loss) - It turn off mode.		detection/Video loss) – It erases alarm output.
No response in Live screen even FUNC [TOOLS - PTZ] button is pressed. External HDDs are not recognized as quantity installed physically after connecting multiple external HDDs to DVR. "HDD FAIL" icon and error message pops up. "Hease check HDD connection status. Please contact local dealer if this message continues to pop up even if there is no problem in connection. "Please check if additional HDD is compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. Please check if additional storages are compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. Please encort of product manual for details "Please refer to UPDP section under "Network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection and setup. "Please enter to UPDP section under "Network connection and setup" is user is using router for network connection. "Please heck if		3) For event cancel : Event record mode - Alarm (Motion
Correctly for PTZ camera in Menu -> Device -> PTZ.		detection/Video loss) – It turn off mode.
External HDDs are not recognized as quantity installed physically after connecting multiple external HDDs to DVR. "HDD FAIL" icon and error message pops up. "Hobe Fail icon and error message pops up. "Hobe is no added information of HDD after installing additional HDD. "Hease contact local dealer if this message continues to pop up even if there is no added information of external storage devices (USB memory, eSATA HDD). Network setup using router is difficult. "Please check if additional storages are compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. "Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Lost password. "Please contact CS team of manufacturer. "Please don't remove media during copy or don't turn off DVR. "Fease install multi codec for playback data copied in avi format. "Please install multi codec for playback data copied in avi format. Please check if camera input is well connected "Please check HDD is ready for record. "Please check if camera input is well connected "Please check if camera input is we	No response in Live screen even FUNC	✓ Check if connected protocol and other configuration is set
later. If same problem goes on, it is highly originated from HDD problem. Please try it with other HDD problem. Please contact CS team of manufacture. Please check if additional HDD is compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. Please trefer to UPnP section under "Network connection and setup" if a user is using router for network connection and setup" if a user is using router for network connection. Please trefer to UPnP section under "Network connection and setup" if a user is using router for network connection. Please don't remove media during copy or don't turn off DVR.	[TOOLS - PTZ] button is pressed.	correctly for PTZ camera in Menu -> Device -> PTZ.
connecting multiple external HDDs to DVR. "HDD FAIL" icon and error message pops up. Please check HDD connection status. Please contact local dealer if this message continues to pop up even if there is no added information of HDD after is no added information of HDD after is no added information of external storage devices (USB memory, eSATA HDD). Network setup using router is difficult. Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection and setup" if a user is using router. Copied data is not played in the PC. Copied data is not played in the PC. Can't return to live mode during playback. Recording is not working. Please check if camera input is well connected Please check if camera input is well connected Please check if current time is included in scheduled record time in case record mode is continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status. Recorded picture quality is not good. Please set picture quality as Q7 for 1080p, Q5 for 720p.	External HDDs are not recognized as	✓ It takes time to be recognized multiple external HDDs. Try it again
There is no added information of HDD after installing additional HDD. There is no added information of WP lease check if additional HDD is compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. There is no added information of external storage devices (USB memory, eSATA HDD). Network setup using router is difficult. Yelease check if additional storages are compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. Yelease refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Lost password. Yelease contact CS team of manufacturer. Yelease check if camera input is well connected. Yelease check	quantity installed physically after	later. If same problem goes on, it is highly originated from HDD
"HDD FAIL" icon and error message pops up. Please contact local dealer if this message continues to pop up even if there is no problem in connection. There is no added information of HDD after installing additional HDD. There is no added information of external storage devices (USB memory, eSATA HDD). Network setup using router is difficult. Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Lost password. Copied data is not played in the PC. Copied data is not played in the PC. Can't return to live mode during playback. Recording is not working. Please check if additional HDD is compatible with DVR. To know more about compatibility, please contact CS team of manufacturer. Please refer to product manual for details Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection. V Please contact CS team of manufacturer. V Please don't remove media during copy or don't turn off DVR. V VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. Please install multi codec for playback data copied in avi format. Can't return to live mode during Press [] or [live] button in front panel or remote control to return to live screen. Recording is not working. Please check if camera input is well connected Please check HDD is ready for record. Please check HDD is ready for record. Please check HDD is ready for record. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status.	connecting multiple external HDDs to	problem. Please try it with other HDD
Please contact local dealer if this message continues to pop up even if there is no added information of HDD after installing additional HDD. There is no added information of HDD after installing additional HDD. There is no added information of external storage devices (USB memory, eSATA HDD). Network setup using router is difficult. Network setup using router is difficult. Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Lost password. Copied data is not played in the PC. Yelease don't remove media during copy or don't turn off DVR. Yelease install multi codec for playback data copied in avi format. Can't return to live mode during playback. Recording is not working. Please check if camera input is well connected Please check if camera input is well connected Please check if current time is included in scheduled record time in case record mode is continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status. Recorded picture quality is not good. Please set picture quality as Q7 for 1080p, Q5 for 720p.	DVR.	
if there is no problem in connection. There is no added information of HDD after installing additional HDD. There is no added information of HDD after installing additional HDD. There is no added information of external storage devices (USB memory, eSATA HDD). Network setup using router is difficult. Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Please contact CS team of manufacturer. Please don't remove media during copy or don't turn off DVR. VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. Please install multi codec for playback data copied in avi format. Please install multi codec for playback data copied in avi format. Press [] or [live] button in front panel or remote control to return to live screen. Please check if camera input is well connected Please check flDD is ready for record. Please check HDD is ready for record. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status.	"HDD FAIL" icon and error message	✓ Please check HDD connection status.
There is no added information of HDD after installing additional HDD. There is no added information of external storage devices (USB memory, eSATA HDD) Network setup using router is difficult. Network setup using router is difficult. Velease refer to product manual for details Velease refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Lost password. Copied data is not played in the PC. Copied data is not played in the PC. Copied data is not played in the PC. Con't return to live mode during playback. Recording is not working. Please check if camera input is well connected Please check if current time is included in scheduled record time in case record mode is continuous or event. Please or to UPnP section under "Network connection and setup" if a user is using router for network connection. Versa (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. Please install multi codec for playback data copied in avi format. Can't return to live mode during playback. Recording is not working. Please check if camera input is well connected Please check HDD is ready for record. Please check HDD is ready for record. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please check if continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status.	pops up.	Please contact local dealer if this message continues to pop up even
after installing additional HDD. There is no added information of external storage devices (USB memory, eSATA HDD). Network setup using router is difficult. Network setup using router is difficult. Please refer to product manual for details Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Lost password. Copied data is not played in the PC. Copied data is not played in the PC. Please don't remove media during copy or don't turn off DVR. VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. Please install multi codec for playback data copied in avi format. Can't return to live mode during playback. Recording is not working. Please check if camera input is well connected Please check HDD is ready for record. Please check HDD is ready for record. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please check if current time is not working please check event detection status. Recorded picture quality is not good. V Please set picture quality as Q7 for 1080p, Q5 for 720p.		if there is no problem in connection.
There is no added information of external storage devices (USB memory, eSATA HDD) Network setup using router is difficult. Network setup using router is difficult. Please refer to product manual for details Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Please contact CS team of manufacturer. Please don't remove media during copy or don't turn off DVR. VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. Please install multi codec for playback data copied in avi format. Press [] or [live] button in front panel or remote control to return to live screen. Recording is not working. Please check if camera input is well connected Please check if current time is included in scheduled record time in case record mode is continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status. Recorded picture quality is not good. Please set picture quality as Q7 for 1080p, Q5 for 720p.	There is no added information of HDD	✓ Please check if additional HDD is compatible with DVR. To know
external storage devices (USB memory, eSATA HDD) Network setup using router is difficult. Network setup using router is difficult. Please refer to product manual for details Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Lost password. Please contact CS team of manufacturer. Please don't remove media during copy or don't turn off DVR. VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. Please install multi codec for playback data copied in avi format. Can't return to live mode during playback. Press [] or [live] button in front panel or remote control to return to live screen. Please check if camera input is well connected Please check record mode. Please check HDD is ready for record. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status. Recorded picture quality is not good. Please set picture quality as Q7 for 1080p, Q5 for 720p.	after installing additional HDD.	more about compatibility, please contact CS team of manufacturer.
eSATA HDD) Network setup using router is difficult. Please refer to product manual for details Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Lost password. Please contact CS team of manufacturer. Please don't remove media during copy or don't turn off DVR. VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. Please install multi codec for playback data copied in avi format. Can't return to live mode during Press [or [live] button in front panel or remote control to return to live screen. Recording is not working. Please check if camera input is well connected Please check HDD is ready for record. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status. Recorded picture quality is not good. Please set picture quality as Q7 for 1080p, Q5 for 720p.	There is no added information of	✓ Please check if additional storages are compatible with DVR. To
Network setup using router is difficult. Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Please contact CS team of manufacturer. Please don't remove media during copy or don't turn off DVR. VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. Please install multi codec for playback data copied in avi format. Press [or [live] button in front panel or remote control to return to live screen. Recording is not working. Please check if camera input is well connected Please check record mode. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status. Recorded picture quality is not good. Please set picture quality as Q7 for 1080p, Q5 for 720p.	external storage devices (USB memory,	know more about compatibility, please contact CS team of
V Please refer to UPnP section under "Network connection and setup" if a user is using router for network connection. Lost password. ✓ Please contact CS team of manufacturer. ✓ Please don't remove media during copy or don't turn off DVR. ✓ VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. ✓ Please install multi codec for playback data copied in avi format. Can't return to live mode during ✓ Press [□] or [live] button in front panel or remote control to return to live screen. Recording is not working. ✓ Please check if camera input is well connected ✓ Please check record mode. ✓ Please check HDD is ready for record. ✓ Please check if current time is included in scheduled record time in case record mode is continuous or event. ✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p.	eSATA HDD)	manufacturer.
setup" if a user is using router for network connection. V Please contact CS team of manufacturer. V Please don't remove media during copy or don't turn off DVR. V VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. V Please install multi codec for playback data copied in avi format. Can't return to live mode during V Press [or [ive] button in front panel or remote control to return to live screen. Recording is not working. V Please check if camera input is well connected V Please check record mode. V Please check record mode. V Please check if current time is included in scheduled record time in case record mode is continuous or event. V Please press FUNC [TOOL – MANUAL RECORDING] button to start record. V In case event record is not working please check event detection status. Recorded picture quality is not good. V Please set picture quality as Q7 for 1080p, Q5 for 720p.	Network setup using router is difficult.	✓ Please refer to product manual for details
Lost password. V Please contact CS team of manufacturer. V Please don't remove media during copy or don't turn off DVR. VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. Please install multi codec for playback data copied in avi format. Can't return to live mode during playback. Recording is not working. Please check if camera input is well connected Please check HDD is ready for record. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status. Recorded picture quality is not good. Please set picture quality as Q7 for 1080p, Q5 for 720p.		✓ Please refer to UPnP section under "Network connection and
Copied data is not played in the PC. Please don't remove media during copy or don't turn off DVR. VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. Please install multi codec for playback data copied in avi format. Can't return to live mode during playback. Press [] or [live] button in front panel or remote control to return to live screen. Please check if camera input is well connected Please check record mode. Please check HDD is ready for record. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status. Recorded picture quality is not good.		setup" if a user is using router for network connection.
 ✓ VFS4 (For DVD copy), exe copy is for customized player only so it can be played using MiniPlayer. ✓ Please install multi codec for playback data copied in avi format. Can't return to live mode during playback. ✓ Press [□] or [live] button in front panel or remote control to return to live screen. Recording is not working. ✓ Please check if camera input is well connected ✓ Please check HDD is ready for record. ✓ Please check if current time is included in scheduled record time in case record mode is continuous or event. ✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p. 	Lost password.	✓ Please contact CS team of manufacturer.
can be played using MiniPlayer. ✓ Please install multi codec for playback data copied in avi format. Can't return to live mode during playback. Recording is not working. ✓ Please check if camera input is well connected ✓ Please check record mode. ✓ Please check HDD is ready for record. ✓ Please check if current time is included in scheduled record time in case record mode is continuous or event. ✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p.	Copied data is not played in the PC.	✓ Please don't remove media during copy or don't turn off DVR.
 ✓ Please install multi codec for playback data copied in avi format. ✓ Can't return to live mode during playback. ✓ Press [□] or [live] button in front panel or remote control to return to live screen. ✓ Please check if camera input is well connected ✓ Please check record mode. ✓ Please check HDD is ready for record. ✓ Please check if current time is included in scheduled record time in case record mode is continuous or event. ✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p. 		✓ VFS4 (For DVD copy), exe copy is for customized player only so it
Can't return to live mode during playback. Recording is not working. ✓ Please check if camera input is well connected ✓ Please check record mode. ✓ Please check HDD is ready for record. ✓ Please check if current time is included in scheduled record time in case record mode is continuous or event. ✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p.		can be played using MiniPlayer.
playback. Recording is not working. Please check if camera input is well connected Please check record mode. Please check HDD is ready for record. Please check if current time is included in scheduled record time in case record mode is continuous or event. Please press FUNC [TOOL – MANUAL RECORDING] button to start record. In case event record is not working please check event detection status. Recorded picture quality is not good. Verease set picture quality as Q7 for 1080p, Q5 for 720p.		✓ Please install multi codec for playback data copied in avi format.
Recording is not working. ✓ Please check if camera input is well connected ✓ Please check record mode. ✓ Please check HDD is ready for record. ✓ Please check if current time is included in scheduled record time in case record mode is continuous or event. ✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p.	Can't return to live mode during	✓ Press [□] or [live] button in front panel or remote control to return
 ✓ Please check record mode. ✓ Please check HDD is ready for record. ✓ Please check if current time is included in scheduled record time in case record mode is continuous or event. ✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p. 	playback.	to live screen.
 ✓ Please check HDD is ready for record. ✓ Please check if current time is included in scheduled record time in case record mode is continuous or event. ✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p. 	Recording is not working.	✓ Please check if camera input is well connected
 ✓ Please check if current time is included in scheduled record time in case record mode is continuous or event. ✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p. 		✓ Please check record mode.
case record mode is continuous or event. ✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p.		✓ Please check HDD is ready for record.
 ✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p. 		✓ Please check if current time is included in scheduled record time in
record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p.		case record mode is continuous or event.
record. ✓ In case event record is not working please check event detection status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p.		✓ Please press FUNC [TOOL – MANUAL RECORDING] button to start
status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p.		·
status. Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p.		
Recorded picture quality is not good. ✓ Please set picture quality as Q7 for 1080p, Q5 for 720p.		<u> </u>
	Recorded picture quality is not good.	
	-	

	will become high accordingly so HDD capacity will be reduced too.
	It will lead to short period time of recording
Remote control doesn't work.	✓ Point to remote control receiver
	✓ Get new batteries.

Compatible HDD

Please ask to seller for the HDD list compatible with DVR.

Factory default set-up values *

	Time		Current time
	Time zone		UTC 00:00 Dublin
	Daylight Saving Time (DST)		off
	Daylight Saving Time (231)	type	Use Day of Week
	Set Custom DST	Start time	Jan / Last / Sun / 0:00
	Set custom 251	End time	Feb / Last / Sun / 0:00
Date/time	Date Format	LIIG time	Month/Day/Year
	Sync With NTP	NTP Enable	Off
	Sync With IVII	NTP Mode	Client
		NTP Location	Public
		NTP Local	0.0.0.0
		Interval	1 hour
	Disk manager	Interval	Tiloui
	RAID manager		
Disk	Overwrite		On
DISK	Block Playback		off / 5Day
	Delete Data		off
	User		admin
	Change ID & PW		udillii.
	Channel Rights		All Select
User Setup	Action Rights		All Select
	netion rights	Auto Login	On / admin
	Additional User Setup	Auto Log-Out	Off / 1 Min
	DVR Alias	Auto Log Out	DVR0
	Language		English
	Keyboard sound		on
	DVR Keyboard ID		1
	Remote Controller ID		All
	System info		
Utility	Save status		
	System log		
	Firmware upgrade		
	Configuration setting initialization		
	Import configuration		
	Export configuration		
Network	; Export configuration		
	Туре		Ethernet
Network	Automatic Addressing (DHCP)		Off

	IP Address		192.168.0.2
	Net Mask		255.255.255.0
	Gateway		192.168.0.1
	UPnP Port Forwarding		off
	DNS		4.2.2.1 / 0.0.0.0 / 0.0.0.0
	Port		80
	Bandwidth Limit (Mbps)		unlimited
	Video Streaming (RTSP)		Port 554 / Auth On
	IP Filtering		off
	ID		Guest
xDSL	Password		*****
	Status		xDSL is not connected
	activate		Turn off
	status		Not registered
DDNS	URL		mycam.to
	group		none
	Enable		off
	Status		Not registered
WRS	WNS (mycam.to)		On
VVKS	Custom DDNS		off
	Domain		
			Generated unique number
D 1:	Enable		Off
Radius	IP Address		0.0.0.0
	Port		1812
Device			
Camera	status		turn on
	Name		Cam 1 ~ 16
	port		None
PTZ	device		None
	address		1
	baudrate		57600
	port		None
keyboard	device		WKC-100
Reyboard	address		1
	Baudrate		9600
	Auxiliary Enable		on
	Home time		off
Etc	Parity bit		None
	Stop bit		1
	Data bit		8
	Edit "SEQ" key sequence	SEQ 1~16	Cam 1~6
		SEQ Rotation	1~4
	Interval		5 (Sec)
Monitor	Restore after Event popup		off
	Edit "MULTI" Key Sequence	SEQ Rotation	1~5
	Event Popup Enable	324 ((3)400)	off / 3sec
	Audio channel		channel 1 ~ 4
	Video channel		Channel 1 ~ 4
Audio	Audio REC		off
AuuiU			0
	Audio Gain		
	audio output channel		current singl-full video's audio
Text	Port		COM1
	Device		None

	Baudrate		2400	
	Sync Video Channel		Cam1	
	Recording		Off	
	Etc	Parity bit	none	
		Stop bit	1	
		Data bit	8	
	Manual	Header check	off	
		header 1	None	
		header 2	None	
		delimiter	0D0A	
		Time interval(ms)	1000	
		# of lines	20	
net			-	
	activate		Turn on	
	Event check		always	
	Event synchronization	Relay 1	Turn on	
			Normal event source turn off all	
			system event source Turn off all	
			Duration period 10 seconds	
		relay 2	Turn on	
			Normal event source Turn off all	
			system event source Turn off all	
			duration period 10seconds	
		Relay 3	Turn on	
			normal event source Turn off all	
		Relay 4	system event source Turn off all	
			duration period 10seconds	
			Turn on	
			normal event source Turn off all	
			system event source Turn off all	
			duration period 10seconds	
		buzzer	Turn off	
ent			normal event source Turn off all	
			system event source Turn off all	
			duration period 10seconds	
		Email	Turn off	
			normal event source Turn off all	
			system event source Turn off all	
			duration period 2mins	
		FTP	Turn off	
			normal event source Turn off all	
			system event source De-activate	
			duration period immediately	
	E-mail configuration	sender address	receiver@gmail.com	
		Receiver address	Dvr1@dvr.com	
		attach	Turn off	
		SMTP address	SMTP_SERVER	
		SMTP ID	email_id	
		SMTP Password	*****	
	1	SMTP port	25	
		SMTP Auth	Not Use	
	FTP configuration	server IP/URL	FTP_SERVER	
	3	FTP channel		

		ID	ftp_user	
		Password	*****	
	channel		Cam1	
Matian	activate		Turn on	
Motion	Sensitivity		5	
	Area		All Select	
C	activate		Turn on	
Sensor	Sensor		Normal Open	
	Channel		Cam1	
Decemb	Preset	S1~S16	None	
Preset		Motion	None	
		Text	None	
Record				
	Record Mode		Countinuous	
	Program		A	
	Pre Event Duration		1	
D 1	Post Event Duration		1	
Record	Program	Program	A	
		Normal FPS	30	
		Normal Quality	7	
		Event FPS	30	
		Event Quality	7	

^{*} Varies between different models

Product specification

HS1600F-D

VIDEO INPUT			PTZ	
Video input	HD-SDI (SMPT	E 292M), DoubleReach TM	Drotons!-	35 models including C1080, C1080PT-Z20, Pelco-D,
Format	CVBS, 960H		Protocols	Pelco-P, Samsung, Panasonic and others
	HD1080p	1920x1080 / 25, 30 FPS	NETWORK	
	HD720p	1280x720 / 25, 30, 50, 60 FPS	Interface	2 Gigabit Ethernet (10/100/1000Mbps)
Resolution / Frame Rate	DoubleReach	1920x1080 / 25, 30FPS	Туре	Static IP, Dynamic IP, xDSL
Tramertate	510H/760H	720x480 / 60i or 720x576 / 50i	DDNS	WNS, DynDNS, NoIP, WRS
	960H	960x480 / 60i or 960x576 / 50i	Bandwidth limit	Supported
Connectors	16ch, 75Ω BN0		NTP	Server / Client / Both
VIDEO OUTPUT			Users	10 Monitoring, 2 Playback
		1, 4, 9, 10, 13, 16 split-screen		H.264 stream, High resolution
	HDMI	1920 x 1080	Streaming	1 additional H.264 stream, Normal resolution
	VGA	User-defined display / Alarm pop-up		1 JPEG stream, Normal resolution for e-mail or mobile
Video output		1, 4, 9, 10, 13, 16 split-screen	SECURITY	
	BNC	CVBS	User level	1 admin, 10 users
		Channel Switching / Alarm pop-up	User privilege	Menu, PTZ, Relay, Playback, Power, Copy, Network MIC
RECORDING		Onarmer Switching / Alarm pop-up	IP filtering	Supported
Compression	H.264 / JPEG		STORAGE & BA	ACKUP
Resolution		280 x 720, 720 x 480(576), 960 x 480(576)	Storage devices	5 internal SATA HDDs, 1 external eSATA Interface, 1 Gigabit network for storage(NS04R)
Rate		ps) per channel	File system	Proprietary file system, Data-loss protection against power-failure
Quality	10 levels up to	nt / Schedule & Event / Continuous & Event	Capacity	Max. 32TB with eSATA, Max. 128TB with cascaded NS04R
Mode Schedule		it / Scriedule & Everit / Continuous & Everit	Backup type	Multi-channel or Single channel avi file
PLAYBACK	24hrs / 7days		Backup device	USB drive (2 ports)
Mode	Instant Playbac	ck / Soarch	S.M.A.R.T.	Temperature and Health checking
		ips) per channel	SERIAL & I/O	
Speed Search type			Serial port	1 RS-232C, 2 RS-485
Block playback	Date/Time, Calendar/Time-line, Event, Thumbnail, Text 24hours ~ 99days		Sensor input	16 Dry-contacts
EVENT & ALAR	•		Relay output	4 Relays
Event source		tection), Sensor, Text, Video Loss	CONTROLLER	
Event check	,	today, oction, real, video Loss	Device	IR remote controller, Joystick Keyboard, Mouse
Schedule	24hrs / 7days	5 7 5TD N	SOFTWARE	
Event action		E-mail, FTP, Alarm pop-up	Web viewer	Monitoring / Event / PTZ / Playback for IE
MD area	15 x 10		Java viewer	Monitoring / Event / PTZ for IE, Chrome, Safari
Sensor input	, ,	O or NC selectable)	Mobile viewer	Monitoring / PTZ / LogView / Playback with iPhone & Android
Text input		port, AVE VSI Pro/Hydra support	CMS	Control Center, Max. 1024 DVRs
SYSTEM ALARI			SDK	ActiveX(COM) SDK
Alarm source	· ·	almost full, Fan fail, Password fail, WRS fail		TAL & PHYSICAL
Alarm action	Warning mess	age, Buzzer, E-mail, Relay	Dimension	445(W) x 418(D) x 88(H) mm
AUDIO			Weight	10 Kg (No HDD)
nput/output		HDMI & RCA output	Operating	5°C~45°C (41°F~ 113°F)
Compression	,	ps, 16KHz, 16bit sampleing)	Temperature	·
Direction	Both		Power	AC free volt (100 ~ 240VAC), 50/60Hz
			Consumption	Max. 100W, Typical 70W (1 HDD)
			Approval	KC, FCC, CE, RoHS

HSC1601F-D


CVBS, 960H Protocols Pelcol	odels including C1080, C1080PT-Z20, Pelco-D, -P, Samsung, Panasonic and others abit Ethernet (10/100/1000Mbps) IP, Dynamic IP, xDSL	
CVBS, 960H Felico Felico	abit Ethernet (10/100/1000Mbps)	
Resolution Frame Rate HD720p 1280x720 / 25, 30, 50, 60 FPS Interface 1 Giga Type Static		
Resolution / Frame Rate		
Frame Rate	IP, Dynamic IP, xDSL	
510H/760H 720X480 760I 0F 720X576 750I Bandwidth limit Suppo		
Bandwidth limit Suppo	, DynDNS, NoIP, WRS	
960H 960x480 / 60i or 960x576 / 50i		
Connectors 16ch, 75Ω BNC connector	er / Client / Both	
VIDEO OUTPUT	onitoring, 2 Playback	
1, 4, 9, 10, 13, 16 split-screen	stream, High resolution	
HDMI VGA 1920 x 1080 Streaming 1 add	itional H.264 stream, Normal resolution	
User-defined display / Alarm pop-up	EG stream, Normal resolution for e-mail or mobile	
Video output 1, 4, 9, 10, 13, 16 split-screen		
BNC CVBS User level 1 adm	nin, 10 users	
User privilege Menu,	, PTZ, Relay, Playback, Power, Copy, Network MIC	
RECORDING IP filtering Support	orted	
Compression H.264 / JPEG STORAGE & BACKUP		
Resolution 1920 x 1080, 1280 x 720, 720 x 480(576), 960 x 480(576) Storage devices 2 inter	rnal SATA HDDs, 1 external eSATA Interface,	
Rate Max 3uths(25ths) per channel File system	ietary file system, Data-loss protection against r-failure	
Quality 10 levels up to 12Mbps Capacity Max.	32TB with eSATA	
Mode Manual & Event / Schedule & Event / Continuous & Event Backup type Multi-	channel or Single channel avi file	
Schedule 24hrs / 7days Backup device USB of	drive (2 ports)	
PLAYBACK S.M.A.R.T. Temp	perature and Health checking	
Mode Instant Playback / Search SERIAL & VO		
Speed Max. 30fps(25fps) per channel Serial port 1 RS-	-232C, 2 RS-485	
Search type Date/Time Calendar/Time-line Event Thumbnail Text	y-contacts	
Block playback 24hours ~ 99days Relay output 2 Relay	ays	
EVENT & ALARM CONTROLLER		
Event source MD(Motion Detection), Sensor, Text, Video Loss Device IR rer	mote controller, Joystick Keyboard, Mouse	
Event check Schedule 24hrs / 7days SOFTWARE	SOFTWARE	
Event action Buzzer, Relay, E-mail, FTP, Alarm pop-up Web viewer Monito	oring / Event / PTZ / Playback for IE	
MD area 15 x 10 Java viewer Monito	oring / Event / PTZ for IE, Chrome, Safari	
Sensor input Dry contact (NO or NC selectable) Mobile viewer Monito	oring / PTZ / LogView / Playback with iPhone & Android	
Toyt input POS/ATM cuppert AVE VSI Pro/Hydra cuppert	rol Center, Max. 1024 DVRs	
SYSTEM ALADM	eX(COM) SDK	
Alarm source HDD fail, HDD almost full, Password fail, WRS fail	· ,	
Alarm action Warning message Buzzer F-mail Relay	V) x 393(D) x 88(H) mm	
AUDIO	(No HDD)	
Input/output 4 RCA input / HDMI & RCA output	·	
Compression ADPCM (32Kbps, 16KHz, 16bit sampleing) 5°C~4	45°C (41°F ~ 113°F)	
Direction Both	2V / 5A	
Consumption	40W, Typ 30W	
Approval KC, F	CC, CE, RoHS	


HSC801F-D


Resolution / Frame Rate	HD-SDI (SMPT CVBS, 960H HD1080p HD720p	E 292M), DoubleReach TM 1920x1080 / 25, 30 FPS	Protocols	35 models including C1080, C1080PT-Z20, Pelco-D, Pelco-P, Samsung, Panasonic and others
Format Resolution /	HD1080p	4020v4000 / 25, 20 EDS	Protocois	Pelco-P. Samsung, Panasonic and others
Resolution / Frame Rate		1020v1000 / 25 20 EDS		,,
Resolution / Frame Rate	HD720p	1920X1000 / 25, 50 FF 5	NETWORK	
Frame Rate		1280x720 / 25, 30, 50, 60 FPS	Interface	1 Gigabit Ethernet (10/100/1000Mbps)
	DoubleReach	1920x1080 / 25, 30FPS	Туре	Static IP, Dynamic IP, xDSL
	510H/760H	720x480 / 60i or 720x576 / 50i	DDNS	WNS, DynDNS, NoIP, WRS
	960H	960x480 / 60i or 960x576 / 50i	Bandwidth limit	Supported
Connectors	8ch, 75Ω BNC	connector	NTP	Server / Client / Both
VIDEO OUTPUT			Users	10 Monitoring, 2 Playback
		1, 4, 9 split-screen		H.264 stream, High resolution
	HDMI VGA	1920 x 1080	Streaming	1 additional H.264 stream, Normal resolution
	VOA	User-defined display / Alarm pop-up		1 JPEG stream, Normal resolution for e-mail or mobile
Video output		1, 4, 9 split-screen	SECURITY	
	BNC	CVBS	User level	1 admin, 10 users
		User-defined display / Alarm pop-up	User privilege	Menu, PTZ, Relay, Playback, Power, Copy, Network MIC
RECORDING		eser defined display / / darm pop ap	IP filtering	Supported
Compression	H.264 / JPEG		STORAGE & BA	CKUP
		280 x 720, 720 x 480(576), 960 x 480(576)	Storage devices	2 internal SATA HDDs, 1 external eSATA Interface,
		ps) per channel	File system	Proprietary file system, Data-loss protection against power-failure
Quality	10 levels up to	12Mbps	Capacity	Max. 32TB with eSATA
Mode	Manual & Even	t / Schedule & Event / Continuous & Event	Backup type	Multi-channel or Single channel avi file
Schedule	24hrs / 7days		Backup device	USB drive (2 ports)
PLAYBACK		S.M.A.R.T.	Temperature and Health checking	
Mode	Instant Playback / Search		SERIAL & I/O	
Speed	Max. 30fps(25f	ps) per channel	Serial port	1 RS-232C, 2 RS-485
Search type	Date/Time, Calendar/Time-line, Event, Thumbnail, Text		Sensor input	8 Dry-contacts
Block playback	24hours ~ 99days		Relay output	2 Relays
EVENT & ALARM		CONTROLLER		
	MD(Motion Det	ection), Sensor, Text, Video Loss	Device	IR remote controller, Joystick Keyboard, Mouse
Event check Schedule	24hrs / 7days		SOFTWARE	
Event action	Buzzer, Relay,	E-mail, FTP, Alarm pop-up	Web viewer	Monitoring / Event / PTZ / Playback for IE
MD area	15 x 10		Java viewer	Monitoring / Event / PTZ for IE, Chrome, Safari
Sensor input	Dry contact (NO	O or NC selectable)	Mobile viewer	Monitoring / PTZ / LogView / Playback with iPhone & Android
Text input	POS/ATM supp	oort, AVE VSI Pro/Hydra support	CMS	Control Center, Max. 1024 DVRs
SYSTEM ALARM	1		SDK	ActiveX(COM) SDK
Alarm source	HDD fail, HDD almost full, Password fail, WRS fail		ENVIRONMENT	
Alarm action	Warning messa	age, Buzzer, E-mail, Relay	Dimension	350(W) x 393(D) x 88(H) mm
AUDIO			Weight	8 Kg (No HDD)
Input/output	4 RCA input / I	HDMI & RCA output	Operating	5°C~45°C (41°F~ 113°F)
Compression	ADPCM (32Kb)	ps, 16KHz, 16bit sampleing)	Temperature	·
Direction	Both		Power	DC 12V / 5A Max. 40W, Typ 30W
			Consumption Approval	KC, FCC, CE, RoHS

Product Dimension


HS1600F-D










HSC1601F-D








HSC801F-D





Open Source License Report on the Product

Open Source License Report on the Product

The software included in this product contains copyrighted software that is licensed under the GPL/LGPL. You may obtain the complete Corresponding Source code from us for a period of three years after our last shipment of this product by sending email to comprected grant complete Corresponding Source code in the physical medium such as CD-ROM, the cost of physically performing source distribution might be charged.

GPL Software: busybox, boa, CyaSSL, dosfstools, linux kernel, rp-ppoe, cdrtools, dvd+rw-tools, dhcpcd, iproules martmonitools.

GPL Software: busybox, boa, CyaSSL, dosfstools, linux kernel, rp-ppoe, cdrtools, dvd+rw-tools, dhcpcd, iproules martmonitools.

Apache License: glibc, libgoc, libstdc++, FFMpeg, ftplib
Apache License: WenQuanyi Micro Hei
Copyright (c) 2007, Google Corpy, Copyright (c) 2008,2009 WenQuanyi Board of Trustees and Qianqian farig.

Apache License: Apache Commons

http://commons.apache.org

BSD License: Apache Commons

http://commons.apache.org

BSD License: asth, miniupnpc, telnet-server, YUI Library, ppp

Freetype License: freetype?

Portions of this software included in this product are copyright (C) 2010 The FreeType Project (www.freetype.org). All rights reserved.

US License: JPEG

The software included in this product is based in part on the work of the Independent JPEG Group.

MIT License: C-ares, curl, liboauth, jcodec

OpenSSL License: OpenSSL

SIL Open Font License: Varimo

Copyright (c) 2010 Google Corporation.

This Font Software is licensed under the SIL Open Font License, Version 1.1.

This license is copied in this manual, and is also available with a FAQ at: http://scripts.sil.org/OFL

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

GIVE GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

not allowed. Preamble
The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most ofhe Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead 1 You in 2nd annohi of it to your programs, too.

into iterities for most sortwaire are designed to take away your freedom to share and change free contract, the GNU General Public License is intended to guarantee your freedom to share and change free contracts, the GNU General Public License is the formation of the Free Software foundations software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead). You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you review source code or can get it if you want it that you can change the software or use pieces of it in new free programs, and that you know you can do these things you to surrhead the representations to the software or use pieces of it in new free programs, and that you know you can do these things you to surrhead the representations to the software or the software or if you most in the your source or the software or use pieces of it in new free programs, and that you know you can do these things or to ask you to surrhead the rights that you have you must show the copies of the software or if you most in the software in the software in the software in the recipients all the rights that you have. You must make sure that they too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy distributed and/or modify the software.

We protect your rights with two steps: (1) copyright the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original author's reputatio

based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interrchange: or.

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or, b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange, or, c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (complier, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

on) of the operating system on which the executable runs, unless that component itself accompanies the executable. If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code. 4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance. 5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it. 6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licenser to copy, distribute or modify the Program operation of the program of th

7. If as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.
If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

circumstances. It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validify of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

Consistent application of that system; it is up to the author/uotinit to decide in the of size is willing to distribute software through any other system and a licensee cannot impose that choice. This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version may be similar in spirit to the present version, but may differ in ticense which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software foundation. If the by the Free Software foundation and the stream of the program should be software foundation. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software winch is copyrighted by the Free Software Foundation, write to the Free Software Foundation, we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

1.1 BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM is SIMITH FOU

If you develop a new program, and you want it to be or the greatest purposes. The sum you can be the series which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program, It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty, and each file should have at least the "copyright" line and a pointer to where the full notice is found, one line to give the program's name and an idea of what it does.

Copyright (C) yyyy name of author

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA, Also add information on how to contact you by electronic and paper mail. If the program is interactive, make it output a short notice like this when it starts in an interactive mode: Gnomovision eversion 69, Copyright (C) wear name of author Gnomovision comes with ABSOLITELY NO WARRANTY; for details type show w'. This is free software, and you are welcome to redistribute it under certain conditions; type show c' for details.

to redistribute it under certain conditions; type 'show c' for details.

The hypothetical commands 'show w' and 'show c' should show the appropriate parts of the General Public License of course, the commands you use may be called something other than 'show w' and 'show c'; they could even be mouse-clicks or menu items--whatever suits your program. You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample, alter the names: Yoyodyne, Inc., hereby disclaims all copyright interest in the program 'Gnomovision' (which makes passes at compilers) written by James Hacker, signature of If Y Coon, 1 April 1989

Ty Coon, President of Vice
This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright 2007 Free Software Foundation, Inc. https://fsforg/

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU GENERAL Public License is a free, copyleft license for software and other kinds of works.

Copyright © 2007 free Sortware Foundation, inc. <a href="figure-structure-st

masks.
"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.
To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying. An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

the user that there is no warranty for the work (except to the extent that warranus are provided increases may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.
The "Source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.
A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.
The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component," in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a complier used to produce the work, or an object code interpreter used to run it.

The corresponding Source for a work in object code form means all the source code needed to script to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition flies associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or contro

means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

4. Conveying Verbatim Copies.

5. Conveying Verbatim Copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program. You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

7. Conveying Modified Source Versions.

8. Conveying Modified Source Versions.

8. The work coust carry uncomment notices stating that you modified it, and giving a relevent date.

8. It was constructed that the conversion of a copy that you convey, and you may conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices." O' you must license will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License given possible in the work and all its parts, regardless of how they are packaged. This License given no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

9. If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interacted with do not display Appropriate Legal Notices; however, if the Program has interacted with do not display Appropriate Legal Notices; however, if the compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work with oth

You may convey a covered work in object code form under the terms of bis license, in one of these ways:

a) Convey the machine-readable Corresponding Source under the terms of this license, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code is a network server, the Corresponding Source way be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintair clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source you remain obligated to ens

object code and Corresponding Source of the work are being offered to the general public at no charge under subsection of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A steparable portion of the object tode, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product," which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling, in determining whether a product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product user or of the way in which the particular user actually uses, or expects or is expected to use, the product or non-consumer uses, unless such uses represent the only significant mode of use of the product. Tinstallation Information for a User Product means any methods, procedures, authorization keys, or other information nequired to install and execute modified versions of a covered work in that User Product from a modified version of its. Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

tunctioning of the modified object code is in no case prevented or interfered with solely because modification has been made. If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed error (regardless of how the transaction is naturacterized), the Corresponding Source conveyed under this section must be accompanied by the Incellation Information. But this requirement does not apply if neither you nor any third party retains the above the product of the product of the product of the work has been installed in SOM.

ROM). The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied whe the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network. Corresponding Source conveyed, and Installation Information provided, in accord with this section must

be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying. 7. Additional Terms. "Additional Terms is a terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law If additional permissions apply only to part of the Program, that part may be used separately be permissions, but the entire Program remains governed by this License without regard to the additional permissions.

permissions, but the entire rrogarian remains governed by an access of the permissions. When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission. Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms. a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License.

or by Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or o; Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or of 0! Limiting the use for publicity purposes of names of licensors or authors of the material; or e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors. All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying. If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

restriction does not survive such relicensing or conveying. If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses gramted under the third paragraph of section 11). However, if you cease all violation of this License, then your license from a particular copyright holder is reliated of provisionally unless and until the copyright holder explicitly and finally terminates your intense prior to 60 days after the cessation. Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License for any workly from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10. 9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this

was may not impose any further restrictions on the essence of the rights granted or affirmed under this License. For example, you may not impose a license fee, royally, or other change for exercise of rights granted under this License, and you may not impose a license fee, royally, or other change for exercise of rights granted under this License, and you may not imitiate litigation (including a cross-claim or counterclaim in alwavit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A 'contributor' is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version." A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed only as a consequence of further modification of the contributor version. For purposes of this mringed only as a consequence of further modification of the contributor version. For purposes of this requirements of this License.

Each contributor grants you a non-exclusive, worldwide, cryostly-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version. For a contributor version. For a contributor of the co

14. Revised Versions of this License.

15. The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

16. Each version is given a distinguishing version number. If the Program specifies that a certain numbered version or is given a distinguishing version number. If the Program applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation. If the Program decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

15. Lisclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND PITHESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU, SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIND PARTIES OR A FAILURE OF THE PROGRAM TO PERATE WITH ANY OTHER PROGRAMS, EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee. PND OF TERMS AND CONDITIONS
If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

To line to give the program's name and a brief idea of what it does. Copyright (C) syear> "came of authors"
This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License and information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

Sprogram> Copyright (C) syear> "name of authors"
This program comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.

This is free software, and you are welcome to redistribute it under certain conditions; type 'show c' for details.

The hypothetical commands show w' and 'show c' should show the appropriate parts of the General Public License of town or program's commands might be different, for a GUI interface, you would use an 'about box'.

You should also get your employer (if you work as a programmer) or scho

IThis is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble
The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change from the contrast the GNU General Public License are intended to guarantee your freedom to share and change it. By contrast, the GNU General Public License is free for all its general public responsibility of the contrast of the contra

seneral Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances. Pror example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License. In other cases, permission to use a particular library in non-free programs enables any greater number of people to use a large body of free software. For example, permission to use the GNU/C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system. Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a 'work based on the library' and a "work that uses the library'. The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

run. Terms and conditions for copying, distribution and modification

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

1. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called 'this License'). Each licensee is addressed as 'you'.

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables. The "Library", below, refers to any such software library or work which has been distributed under these terms. A 'work based on the Library' means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term 'modification').

Source code' for a work means the preferred form of the work for making modifications to it. To a library, complete source code means all the source code for all modules it contains, plus any associated interface definition flies, plus the scripts used to control compilation and installation of the library. Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in diependent of the use of the Library in (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that tuses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in

any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty, keep intact all the notices that refer to this License and to the absence of any warranty and distribute a copy of this License along with the Library. You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

3. The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application obes not supply such function or table, the facility sill operates, and performs whatever part of its purpose remains meaningful. (For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application supplications. Therefore, Subsection 2d requires that any applications applications to the modifier work as a whole. If identifiable sections of that work are not function must still compute square roots.

These equirement apply to the modifier work as a whole if identifiable sections of that work as separate works. In the modifier of the application of the work in the modifier of the performance of the performance of the p

refer to the ordinary CNU, General Public Lerenée, version 2, instead of to this Leicnes (if) a newer version instead in you wish) Do not make any other change in these notices.

Once this change is made in a given copy, it is inversible for that copy, so the ordinary CNU General This coption is useful when you wish to copy part of the code of the blury into a program that is not a library. This coption is useful when you wish to copy part of the code of the blury into a program that is not a library. The complete corresponding machine-readable source code, which must be distributed under the terms of Section 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medicum customarily used for software interchange. Backet them offering equivalent access to copy the source code even of the complete corresponding and a complete corresponding or the complete corre

License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only

in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

3. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation. If the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, with the conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation, we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE. THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY *AS IS* WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY AND PERFORMANCE OF THE LIBRARY SWITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU AND SUMBERT HOLDER, GAND FITHESS FOOR A PARTICULAR PURPOSE. THE EITHER GISK AS TO THE COLLITY AND PERFORMANCE OF THE LIBRARY SWITH YOU.

DAMAGES.

END OF TERMS AND CONDITIONS

END OF TERMS AND CONDITIONS

If you develop a new library, and you want to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

recommend manight five Solivate and everyone can recishibute and charge, four can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply the terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the copyright line and a pointer to where the full notice is found.

One provided of the control of the

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

Definitions

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "You") shall mean an individual or Legal Entity exercising permissions granted by this License. "Source" form shall mean the preferred form for making modifications, including but not limited to compiled object configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship, For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely lifts (or bind by name) to the interfaces of the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship, including the original version of the Work and any modi

incorporated within the Work constitutes direct or contributory patent intringement, urien any patent incorporated within the Work constitutes directly and the date such litigation is filed.

A Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

1. You must give any other recipients of the Work or Derivative Works a copy of this License; and 2. You must cause any modified files to carry prominent notices stating that You changed the files; and 3. You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and 4. If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works, in at least one of the following places: within a NoTICE text file distributed as part of the Derivative Works, within the Source form or documentation, if provided along with the Derivative Works, or within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own copyright statement to Your modifications and may privide didtional or different New Your thanks and conditions stated in this License.

You may add Your own copyright statement to Your modifications and may privide didtional or different license terms and conditions stated in this License.

Submitted for inclusion in the Work by

7. Disclaimer of Warranty, Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MRCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and search of the provided of

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. Neither the name of the author may be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANITES, INCLIDING, BUT NOT LIMITED TO, THE IMPLIED WARRANITES OF MERCHANITABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES MIXLUDING, BUT NOT LIMITED TO, THE STATE OF THE OPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES MIXLUDING, BUT NOT LIMITED TO, PROCINEMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, OR PROFITS; OR BUSINESS INTERRUPTION HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY OR FORT IN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. Itelent-server license:
Copyright (c) 1939 Regents of the University of California. All rights reserved in source and binary forms, with or without modification, are permitted provided that the following disclaimer.

I Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistribution and use in source and emet.

In the following conditions are met:

I. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

I. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. All advertising materials mentioning features or use of this software must display the following acknowledgement.

This product includes software developed by the University of California, Berkeley and its contributors.

4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

HAPLED WARRANTIES, INCLUDING, BUT NOT ILMITED TO THE MPLIED WARRANTIES OF MERCHANTABILITY AND ETINESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL ETIL REGENTS OR CONTRIBUTIONS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL EXEMPLARY OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT ILMITED TO, PROCUMENTAL, SPECIAL EXEMPLARY OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT ILMITED TO, PROCUMENTAL, SPECIAL EXEMPLARY OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT ILMITED TO, PROCUMENTAL). SPECIAL EXEMPLARY OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT ILMITED TO, PROCUMENTAL OR SPECIAL EXEMPLARY OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT ILMITED TO, PROCUMENTIAL OR TORT (INCLUDING INCLEGNEC OR OR THE PROSIBILITY OF SUCH DAMAGE.

VILLUENCE:

COPYRIGHT (C) 2011, Yahool Inc.

All rights reserved.

Redistribution and use of this software in source and binary forms, with or without modification, are permitted provided that the following conditions are met.

Redistributions of source code must retain the above copyright notice, this list of conditions and the Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the redistributions in binary form

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. Neither the name of Valool Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission of Valool Inc.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTIORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABLITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WAR PORTING OR STRICT LIABILITY, OR TORT (INCLUDING) RIGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. ppp licenses: Copyright (c) 1993 The Australian National University.

All rights reserved. Redistribution and use in source and binary forms are permitted provided that the above copyright notice and this paragraph are duplicated in all such forms and that any documentation, advertising materials, and other materials related to such distribution and use acknowledge that the software was deeploped by the Australian National University. The name of the University may not be used to endorse or promote products derived from this software without specific prior written permission.

HILSOFTWARE IS MOVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Copyright (c) 1939 Carnegie Mellon University.

All rights reserved.

Redistribution and use in source and binary forms are permitted provided that the above copyright notice and this paragraph are duplicated in all such forms and that any documentation, advertising materials, and other materials related to such distribution and use acknowledge that the software was developed by Carnegie Mellon University. The name of the University may not be used to endorse or promote products derived from this software without specific prior written permission.

INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTIBILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Copyright 1998 by the Massachusetts Institute of Technology. Permission to use, copy, modify, and distribute this software and its documentation for any purpose and

without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of M.I. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

M.I. makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

curl license:

M.I.I. makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty. curl license:
Copyright (c) 1996 - 2010, Daniel Stenberg, <daniel@haxx.se>.

All rights reserved.
Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies. THE SOFTWARE IS PROVIDED "AS IS" WITHOUT WARRANIY OF ANY KIND, EXPRESS OR IMPLICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHER DEALINGS IN THE SOFTWARE.
Scrept as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization of the copyright holder.

Ilboauth license:
Unless otherwise indicated, Source Code is licensed under MIT license.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and essociated documentation files (the "Software," to add sisting the software and without Imitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software.

In Software and to permit persons to whom the Software is furnished to do so, subject to the formation of the Software.

HE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANITY OF ANY KIND, EXPRESS OR IMPLIED, INCLIDING BUT NOT ILMITED TO THE WARRANITES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR DAY AND NONINFRINGEMENT IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OTHER DEALINGS IN THE SOFTWARE.

ON THE PROVIDED "AS IS", WITHOUT WARRANITY OF ANY KIND, EXPRESS OR IMPLIED, INCLIDING BUT NOT ILMITED TO THE WARRANITES OF MERCHANTABILITY, FIT

icodec license:

Copyright (C) 2011 The jcodec project. http://code.google.com/p/jcodec/

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, subliciense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial

associated documentation flies (the "Software"), to deal in the Software without Institute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

The Software and the Service and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDER'S BE LIABLE FOR ANY CLAMP, DAMAGES OR OTHER LIABLITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHER WARLINGS IN THE SOFTWARE.

OPENSSL License.

COPYRIGHT OF SOFTWARE.

OPENSSL LICENSE.

OPENSSL LICENSE.

COPYRIGHT OF SOFTWARE.

OPENSSL LICENSE.

O

This library is free for commercial and non-commercial use as long as the following conditions are aheared to. The following conditions apply to all code found in this distribution, be it the RC4, RSA, lhash, DES, etc., code: not just the SSL code. The SSL documentation included with this distribution is covered by the same copyright termis except that the holder is Tim Hudson (tjh@cryptsoft.com). Copyright remains Ficr Young's, and as such any Copyright notices in the code are not to be removed. If this package is used in a product, Eric Young should be given attribution as the author of the parts of the library used. This can be in the form of a textual message at program startup or in documentation (online or textual) provided with the package. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1.Redistributions of source code must retain the copyright notice, this list of conditions and the following disclaimer.

1.Redistributions of source code must retain the copyright notice, this list of conditions and the following disclaimer.
2.Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3.All advertising materials mentioning features or use of this software must display the following acknowledgement:
"This product includes cryptographic software written by Eric Young (eay@cryptsoft.com)"
The word 'cryptographic' can be left out if the rouines from the library being used are not cryptographic related:).

The word 'cryptographic' can be left out if the rouines from the library being used are not cryptographic related:-).

4.If you include any Windows specific code (or a derivative thereof) from the apps directory (application code) you must include an acknowledgement.

"This product includes software written by Tim Hudson (tjh@cryptsoft.com)".

THIS SOFTWARE IS PROVIDED BY ERIC VOLING "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES, LOSS OF USE, DATA, OR PROFITS, OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ANSING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The licence and distribution terms for any publically available version or derivative of this code cannot be changed. i.e. this code cannot simply be copied and put under another distribution licence [including the GNUP Public Licence]

SIL OPEN FONT LICENSE Version 1.1 - 26 February 2007

PREAMBLE

The quals of the Open Font License (OFL) are to stimulate worldwide development of collaborative font

Version 1.1 - 26 February 2007
PREAMBLE
The goals of the Open Font License (OFL) are to stimulate worldwide development of collaborative font projects, to support the font creation efforts of academic and linguistic communities, and to provide a free and open framework in which fonts may be shared and improved in partnership with others. The OFL allows the licensed fonts to be used, studied, modified and redistributed freely as long as they are not sold by themselves. The fonts, including any derivative works, can be bundled, embedded, redistributed and/or sold with any software provided that any reserved names are not used by derivative works. The fonts and derivatives, however, cannot be released under any other type of license. The requirement for fonts to remain under this license does not apply to any document created using the fonts or their derivatives.

EFINITIONS
Font Software' refers to the set of files released by the Copyright Holder(s) under this license and clearly marked as such. This may include source files, build scripts and documentation.

*Reserved Font Name' refers to any names specified as such after the copyright statement(s).

**Original Version' refers to any names specified as such after the copyright statement(s).

**Modified Version' refers to any originative made by adding to electing or substitution.

Original vision.

Holder(s).

"Modified Version" refers to any derivative made by adding to, deleting, or substituting — in part or in whole — any of the components of the Original Version, by changing formats or by porting the Font

*Modified Version reters to any servence whole — any of the components of the Original Version, by changing formats or by porting the Font Software to a new environment.
*Author' refers to any designer, engineer, programmer, technical writer or other person who contributed to the Font Software.
PERMISSION 8 CONDITIONS
Permission is hereby granted, free of charge, to any person obtaining a copy of the Font Software, to use, study, copy, merge, embed, modify, redistribute, and sell modified and unmodified copies of the Font Software, subject to the following conditions:

1) Neither the Font Software nor any of its individual components, in Original or Modified Versions, may be sold by itself.

Software, subject to the following conditions:

Neither the Fort Software nor any of its individual components, in Original or Modified Versions, may be sold by itself.

2) Original or Modified Versions of the Font Software may be bundled, redistributed and/or sold with any software, provided that each copy contains the above copyright notice and this license. These can be included either as stand-alone text flies, human-readable headers or in the appropriate machine-readable metadata fields within text or binary files as long as those fields can be easily viewed by the user.

3) No Modified Version of the Font Software may use the Reserved Font Name(s) unless explicit written permission is granted by the corresponding Copyright Holder. This restriction only applies to the primary font name as presented to the users.

4) The name(s) of the Copyright Holder(s) or the Author(s) of the Font Software shall not be used to promote, endorse or advertise any Modified Version, except to acknowledge the contribution(s) of the Copyright Holder(s) and the Author(s) or with their explicit written permission.

5) The Font Software, modified or unmodified, in part or in whole, must be distributed entirely under this license, and must not be distributed under any other license. The requirement for fonts to remain under this license becomes null and void if any of the above conditions are not met.

DISCLAIMER

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINTRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT IN NO EVENT SHALL THE COPYRIGHT HOLDER BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCUDING ANY GENERAL, SPECIAL, INDIPECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Manufacturer might service at user's cost for following request made by customer.

1. Customer notice.

- ✓ Please make regular schedule to check unit status (Daily check is recommended).
- ✓ Manufacturer will not take any responsibility on the physical/human damage caused by robbery, natural disaster.
- ✓ A/S will include product only manufactured by original manufacturer.
- ✓ Any damage caused during installation will be dealt with installation company.
- ✓ Manufacturer doesn't take any responsibility on wrong specified feature excluded in product manual or described improperly by other shopping mall.
- ✓ Please make sure to backup recorded data as recorded data will be removed while manufacturer repair the unit. Manufacturer will not be responsible for any data loss caused during repair service.
- 2. Service request for product usage.
 - ✓ Service request on signal check according to usage environment, power check, network setting.
- 3. Installation or explanation request on external device to be integrated with this product.
- 4. Simple assemble or disassemble, adjustment and any request for S/W upgrade.
- ✓ Service request for any damage caused by other stuff coming into device.
- ✓ In case of simple adjustment without disassemble.
- ✓ Just for S/W upgrade (not for product repair)

5. Others

- ✓ Any damage comes from carelessness of customer or explanation request for usage. (Please contact manufacturer for consumable parts)
- ✓ Any damage comes from wrong media use and service request for this.
- ✓ Any damage comes from wrong installation.
- **X** We recommend for user to contact (☎+82-1644-3421) before claiming customer service since customer service will require certain amount of cost.

Warranty

Product name	Digital Video Recorder	Warranty term
Model name	HS1600F-D	
	HSC1601F-D	
	HSC801F-D	2 6
Date of purchase	/ /	2 years after purchase
Warranty term	/ /	
Serial number		

Customer's address	Name	
	Contact	
Address of shop(Company name)	Name	
	Contact	

Please fill out vacant area before selling products.

★ For customer service ★

Please read through product manual before claiming customer service.

Any simple malfunctions due to customer's misunderstanding on the product will be fixed by customer's side.

For requesting service?

Please inform details of malfunctions correctly.

Free or non free repair will be decided based on details of warranty card.

WebGate Division Daemyung Enterprise Co., Ltd.

6F Hanlim Venture Town B/D 689-6, Geumjeong Dong, Gunposi, Gyeonggido, Korea

Main : TEL : +82-31-428-9300 Client Service : TEL : +82-1644-3421

The damage coming from following condition will be repaired at customer's cost.

- 1) Any damage comes from customer's carelessness.
- 2) In case not recommended power is entered.
- 3) In case user repair unit at their own.
- 4) Any damage comes from natural disaster (Fire, Flood, etc)
- 5) Consumable parts replacement.







Premium to your **HD-CCTV**

WEBGATE

WEBGATE Div. Daemyung Enterprise Co., Ltd.

TEL +82-31-428-9300 sales@webgateinc.com support@webgateinc.com www.webgateinc.com